

ITEM No. 22
FILE No. XXVIII-35

Classification Cancelled,
by authority of
The Joint Chiefs of Staff,
by Col. J. H. Smith.

COPY NO. 196

~~CONFIDENTIAL~~

**PRODUCTION OF FATTY ACIDS FROM
BY-PRODUCTS OF THE FISCHER-TROPSCH
PROCESS**

Parvuk, P. L.

CONFIDENTIAL

COMBINED INTELLIGENCE OBJECTIVES

SUB-COMMITTEE

CONFIDENTIAL

Report on

PRODUCTION OF FATTY ACIDS FROM BY-PRODUCTS OF THE
FISCHER-TROPSCH PROCESS

Reported by:

P.L. PAVCEK

CIOS Target No. 22/1(1)
Food & Agriculture

COMBINED INTELLIGENCE OBJECTIVES SUB-COMMITTEE
G-2 Division, SHAET (Rear) APO 413

CONFIDENTIAL

3 p. 1

I.G. FARBENINDUSTRIE, LEUNA. FATTY ACID
PRODUCTION BY FISCHER-TROPSCH PROCESS.

Dr. Paul Herold, Director of Research, indicated that Dr. Müller-Conradi or his assistant Dr. Wietzel at the I.G. Farbenindustrie in Oppau (Ludwigshafen) were directly concerned with the production of synthetic fatty acids from by-products of the Fischer-Tropsch process. This process, for the catalytic synthesis of hydrocarbons produces paraffins as a by-product. These paraffins have a m.p. of 50-55°C. and consist of C₂₀-C₂₆ hydrocarbons (average chain length is C₂₂).

~~The paraffins are oxidized with air @ 130-150°C. using K₂Cr₂O₇ as catalyst in aluminium towers. The oxidation is not complete and the Manganese salts of the fatty acids must be separated from the unreacted paraffin. This is accomplished by use of Alcohol and Benzene.~~

The crude fatty acids are neutralized with NaOH or Na₂CO₃. The crude soaps are then subjected to steam distillation at 250°C. (Pressure). The lower fatty acids such as formic, acetic, propionic and butyric acid, come off immediately and the hydroxy acids are converted to unsaturated acids. Keto acids are also removed at this point. (Hader process.)

The olefinic and saturated acids, which remain as the sodium salts from the above distillation, are liberated with HNO₃ and the NaNO₃ removed. The free acids are steam distilled by the "Wecker" method of forcing water into the hot fat. This method avoids polymerization and keto acid formation and high grade fatty acids are obtained.

The fatty acids are esterified with glycerol to form soaps or edible tri-glycerides. Polymerized residue is used in pitching beer barrels by the brewing industry.

Glycerol is made at the I.G. Farben plant in Heydebreck of which a pilot plant is available in Oppau. Propylene is used as the starting material and the usual steps of alcohol → chlorhydrin → glycerol are employed. Glycerol can also be made by direct hydrogenation (nickel catalyst) of glucose or "Invert" sugar. A mixture of glycols results by this procedure.