



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>5</sup> :</b>  <b>C07C 69/30, 69/33</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 91/15455</b>  <b>(43) International Publication Date:</b> 17 October 1991 (17.10.91)
<b>(21) International Application Number:</b> PCT/GB91/00491 <b>(22) International Filing Date:</b> 28 March 1991 (28.03.91)  <b>(30) Priority data:</b> 9007193.7                      30 March 1990 (30.03.90)                      GB  <b>(71) Applicants (for all designated States except US):</b> EXXON CHEMICAL LIMITED [GB/GB]; Exxon Chemical Technology Centre, P.O. Box 1, Abingdon, Oxfordshire OX13 6BB (GB). EXXON CHEMICAL PATENTS INC. [US/US]; 200 Park Avenue, Florham Park, NJ 07932 (US).  <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only) :</b> BENDA, Rainer [DE/BE]; Avenue Salome 18, B-1150 Brussels (BE). GODWIN, Allen, David [US/BE]; Avenue de l'Orangerie, B-1410 Waterloo (BE). WALLAERT, Bernard, Victor, Raimond [FR/FR]; 40, rue de la Plaine, F-76240 Bonsecours (FR).		<b>(74) Agents:</b> BAWDEN, Peter, Charles et al.; Exxon Chemical Limited, Exxon Chemical Technology Centre, P.O. Box 1, Abingdon, Oxfordshire OX13 6BB (GB).  <b>(81) Designated States:</b> AT (European patent), BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, KR, LU (European patent), NL (European patent), SE (European patent), US.  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
<b>(54) Title:</b> ESTERS AND FLUIDS CONTAINING THEM  <b>(57) Abstract</b>  Esters of a C <sub>10</sub> to C <sub>15</sub> branched aliphatic carboxylic acid containing on average more than one branch per molecule in which no more than 20 % of the branching is on the 2 carbon atom, and an aliphatic alcohol having at least three hydroxy groups and their use in lubricant formulations including aqueous formulations or as synthetic oils.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

- 1 -

"Esters and Fluids Containing Them"

The present invention relates synthetic esters and to lubricating compositions containing synthetic esters including aqueous lubricating compositions, the lubricants are especially useful as cutting fluids and hydraulic fluids, and the esters may be used as the oil phase of such fluids, or as additives thereto. The invention also relates to additive concentrates containing such esters for incorporation into such fluids.

Metal-working, or cutting fluids are employed as lubricants and coolants in operations such as, for example, cutting, drilling, milling, tapping, turning, reaming, and grinding. In such operations, it is customary to flood the tool and the workpiece with the fluid to carry off the heat generated. The fluids may be oils or aqueous based fluids containing an organic lubricant which are preferred since they make use of the superior heat transfer capacity of water as well as the lubricity of the organic component.

A problem encountered with aqueous based cutting fluids is there susceptibility to biodegradation. The various additives commonly present in such fluids, for example, corrosion inhibitors, antifoams, extreme pressure agents, antiwear agents, surfactants, and thickeners, generally act as nutrients for microorganisms and even if these organisms do not adversely affect the performance of a fluid, as by

- 2 -

lowering its pH so that it become corrosive to metal or by breaking the emulsion, the proliferation of bacteria or fungi makes the fluid so foul smelling that it must be discarded. Regulations on effluent discharge have added to the desirability of reducing the susceptibility of cutting fluids to biodegradation.

There further remains a need to improve the lubricating properties of cutting fluids, for example by the addition of a specific oiliness agent in the case of solutions, and replacement of some of the proportion of mineral oil by a product having higher lubricating qualities in the case of emulsions. Still further, there remains a need for materials showing improved utility in microemulsions, now preferred because of their stability, the small size of the organic disperse phase particles reducing the tendency to coalesce.

We have now found that certain esters may be used to improve the properties, especially the lubricity, of such materials and that these esters have superior viscometric properties than comparable prior art esters such as those proposed in Japanese Patent Application 6372260 and United Kingdom Patent 1444826.

The present invention accordingly provides an ester of an aliphatic polyol having at least three hydroxy groups with a C<sub>10</sub> to C<sub>15</sub> branched aliphatic carboxylic acid containing on average more than one branch per molecule in which no more than 20% of the branching is on the 2 carbon atom.

- 3 -

The invention also provides concentrates for addition to oil to form an aqueous emulsion containing at least one such ester as part of the oil phase. The invention further provides a hydraulic fluid, and a metal-working fluid, especially an aqueous metal-working fluid, especially a cutting fluid, containing such ester or esters as part or all of the oil phase. The invention further provides the use of such an ester as a component, especially a lubricity enhancing component, in a cutting fluid.


The invention further provides the use of such esters as synthetic lubricants and as additives to provide lubricity to lubricating compositions which may be natural or synthetic.

The aliphatic polyol used in the production of the ester preferably contains from 4 to 10 more preferably 4 to 6 carbon atoms, there may be used, for example, one or more of trimethylol propane, pentaerythritol, glycerol, trimethylol ethane, sorbitol, dipentaerythritol and other oligomers of pentaerythritol. Of these polyols, those with at least three primary hydroxy groups such as pentaerythritol and trimethylol propane are preferred. It is also preferred that the polyol be fully esterified by the acid.

The aliphatic polyhydroxy compound may contain no functional groups other than hydroxy groups, or it may contain other functional groups, for example amine groups. It is preferably free, however, from sulphur-containing substituents.

- 4 -

The acids are preferably monocarboxylic acids of the formula



\* being the 2 carbon atom and may be produced by the oxo process, in which one or more olefinically unsaturated hydrocarbons are hydroformylated by reaction with synthesis gas (hydrogen and carbon monoxide, usually in a weight ratio between 0.9 : 1 to 1.5 : 1) in the presence of a catalyst, generally a cobalt carbonyl, at elevated temperature and pressure (typically between 125°C and 175°C, and 150 to 300 atmospheres) to form an aldehyde with one more carbon atom than the feedstock olefin. The resulting aldehyde is subsequently oxidized to the corresponding acid. The feedstock olefin normally contains a substantial proportion of branched hydrocarbons but, in any event, the reactions taking place during the oxo process cause the product to have a highly branched structure and normally a mixture of such highly branched structures. For example, the tridecanoic acid is a mixture of trimethyldecanoic acids, tetramethylnonanoic acids and dimethyl undecanoic acids with branching distributed along the alkyl group.

Typically such acid mixtures contain less than 40% generally less than 20% and frequently less than 10% by weight of linear acids, less than 20% by weight of acids branched on the 2 carbon (the carbon atom  $\alpha$  to the carboxy

- 5 -

group) and the content of acids branched on carbon 3 or higher is equal to or higher than 40% by weight. The acids also preferably have, on average, more than 2, typically between 2 and 4 branches per molecule and the branches are generally short chain ( $C_1$ - $C_4$ ) usually methyl or ethyl groups. The branching is measured by proton NMR typically using a 220 megahertz machine.

Advantageously, the acid contains from 11 to 13 carbon atoms. For reasons of availability and economics, preferred acids are the  $C_{11}$  and  $C_{13}$  acids; the latter as normally available commercially, and as preferably used in the present invention, is a mixture of  $C_{12}$  and  $C_{13}$  acids.

The esters may be prepared by standard esterification techniques generally reacting one mole of acid for each hydroxy group in the aliphatic alcohol.

It is within the scope of the invention to use esters of acids that have been prepared by means other than the oxo process, provided they are multibranched acids within the definition of the invention, and more especially mixtures of multibranched acids, corresponding to those resulting from the oxo process. Such a procedure is not, however, at present economically favourable compared with the use of materials derived from the oxo process.

An emulsion concentrate within the invention comprises an aqueous dispersion of at least one ester according to the invention, and more especially comprises the ester, an emulsifier, and water, optionally together with other

- 6 -

components normally present in cutting or hydraulic fluids. Such a concentrate will normally have from 10 to 80%, advantageously from 20 to 75%, preferably from 50 to 75%, by weight of active ingredients, the remainder being water. The concentrate may be readily diluted, as by the end user, with more water to give the hydraulic or cutting fluid of the invention, which latter may contain 0.1 to 15%, advantageously 0.5 to 10%, and preferably 0.5 to 5%, by weight of active ingredients, the remainder being water. The emulsions may be water in oil or oil in water emulsions, most preferred are the oil in water emulsions containing from 1 to 10 wt% preferably 2 to 5 wt% oil.

In general, the hydrophilic-lipophilic balance (HLB) of the emulsifier or emulsifiers is matched to that of the base oils or synthetic fluids present, which for a paraffinic oil is in the range of 9.0 and 10.5 while for a naphthenic oil it is between 10.5 and 11.5. Components of emulsifiers with HLB in the range of 5 to 15 may be employed to obtain an appropriate balance.

No change in formulation procedure is necessitated by the inclusion of an ester according to the invention; if any difficulty in dispersion of the ester is encountered a proportion or an increased proportion of emulsifier with HLB in the range of 9 to 11 may be employed.

As suitable emulsifiers there may be mentioned in particular nonionic and anionic surfactants. As examples, there may be mentioned condensates of an alkylene oxide with



- 7 -

an organic compound containing an active hydrogen atom and, generally, at least 6 carbon atoms, for example, a condensate with an alcohol, a phenol, especially an alkyl phenol, a thiol, a primary or secondary amine, or a carboxylic or sulphonic acid or an amide thereof; block copolymers of ethylene and propylene oxide; ethoxylated alkyl phosphates; alkyl sulphates and sulphonates; alkaryl sulphonates and salts thereof; derivatives of polyisobutylene succinic acids and anhydrides; fatty acid salts, and alkanolamines.

The components of the emulsion concentrate may be blended by the procedures normal in the art; no special technique is necessary. As is usual in the art, the components are blended together with stirring at ambient temperature, or slightly above, for example from 40°C to 60°C, for a time sufficient to give a uniform composition. The esters of the present invention being oil-soluble, the concentrate is preferably made by blending the ester with oil or hydrocarbon fluids, adding the emulsifier, and then the water phase containing the water-soluble additives. If necessary, the concentrate is subsequently blended with further water to give the desired active ingredient concentration.

The esters of the invention may be employed in cutting fluids of all types, aqueous systems include white emulsions and, especially, microemulsions, and also in oil-based or other hydrocarbon solvent based metal-working fluids, for example for use in rolling operations.

The esters may be employed as additives which impart mild

- 8 -

extreme pressure and antiwear properties to the lubricant or they may be used as an oil replacement. The emulsion concentrate of the invention will therefore generally contain up to 75% advantageously from 2 to 70%, more preferably 5 to 70%, and most preferably from 10 to 65% by weight of the ester, based on the total weight of the components other than water, the proportion being at the higher end of the range where the ester replaces mineral oil to any extent. These concentrates are typically diluted into water to provide the final fluid containing from 3 to 15 wt% of the concentrate.

The emulsion concentrate, and the resulting hydraulic or metal-working fluid, may contain any or all of the usual additives, e.g., corrosion inhibitors, antifoams, extreme pressure agents, antiwear agents, pour point depressants, antioxidants, thickeners, and biocides. In the examples which follow, however, a simplified system, containing only oil, ester or comparison material, corrosion inhibitor, emulsifier and water, is employed.

The esters may also be used in water free systems, sometimes known as straight oils, there they may be used as an additive to provide lubricity where from 2 to 10% by weight enhances the lubricity of mineral oils or other synthetic oils such as polyalpha olefins. Alternatively the ester may be used to replace mineral oil in which case considerably larger quantities will be used.

- 9 -

Example 1Preparation of the trisundecanoic acid ester  
of trimethylolpropane

To a 3 litre, 3 neck round bottom flask equipped with mechanical stirrer and Dean-Stark trap, are charged 1562.2 g (8.41 moles) of an undecanoic acid produced by oxidation of a C<sub>11</sub> aldehyde is produced by the oxo process (commercially available under the Trade Mark "Cekanoic Oil acid"), 3087.2 g (2.3 moles) trimethylol propane, and 12.2 g p-toluene sulphonic acid as a catalyst. The reaction mixture is purged with nitrogen, then heated to 100°C under a 300 mm Hg vacuum. Over a 3.5 hour period, the reaction temperature is increased to 140°C and the pressure reduced to 100 mm Hg. Water is collected in the Dean-Stark trap, a total of 114 ml being recovered. Heating is continued to collect unreacted acid, the mixture is cooled to 110°C, and 18.7 g sodium carbonate are added. The resulting mixture is stirred for 30 minutes, then 300 ml water are added with stirring and the mixture transferred to a separating funnel.

After the reaction mixture has been allowed to stand, the aqueous layer is drawn off, and then water washing is continued until the aqueous layer tests neutral. Remaining excess acid is removed by steam stripping at 140°C, 200 mm Hg. After stripping, the ester is filtered; yield 1255.8 g. Properties are given in Table 1, following Example 4, under the heading TMP C<sub>11</sub>.

- 10 -

Proton NMR analysis of the aldehyde from which the acid was produced showed it to contain an average of 2.96 methyl containing branches, whilst on Carbon 13 NMR analysis showed that 10.9% branches on the 2 carbon atom, 49.9 on the 3, 23.6 on the 4 and 15.6 on the 5 or higher.

#### Example 2

##### Preparation of the tetraundecanoid acid ester of pentaerythritol

The same procedure was used as in Example 1, using 1499 g (8.06 moles) of the acid, 258.4 g (1.9 moles) of pentaerythritol, and 11.4 g of the catalyst. Properties are given in Table 1, under the heading PE C<sub>11</sub>.

#### Example 3

##### Preparation of the tris tridecanoic ester of trimethylol propane

The same procedure was followed, using 1531.2 g (7.16 moles) of an oxo process tridecanoic acid obtained by oxidation of a C<sub>13</sub> aldehyde obtained by the oxo process, 301.5 g (2.25 moles) of trimethylol propane, and 11.9 g of the catalyst. Properties are given in Table 1, under the heading TMP C<sub>13</sub>. Proton NMR analysis showed it to contain an average of 2.96 methyl containing branches whilst Carbon 13 analysis showed 8.4% of the branches to be in the 2 carbon atom, 47.7 on the 3 carbon, 26.9 on the 4 carbon and 17.0 on the 5 are higher.

- 11 -

Example 4Preparation of the tetra tridecanoic acid ester  
of pentaerythritol

The ester was prepared using the same procedure as in Example 1, from tridecanoic acid and pentaerythritol. Properties are shown in Table 1, below, under the heading PE C<sub>13</sub>.

Table 1

	TMP C <sub>11</sub>	PE C <sub>11</sub>	TMP C <sub>13</sub>	PE C <sub>13</sub>
Acid Number mg KOH/g	0.532	1.53	3.37	1.6
Colour FAC	< 1.	< 1.	< 1.	< 1.
Saponification No., mg KOH/g	261.9	271.7	239.8	248.8
Solidification Point, °C	< -38	< -30	< -36	< -30
Viscosity, cSt 40°C	83.62	160.2	111.16	218.9
Viscosity, cSt 100°C	9.14	13.77	10.91	16.3

- 12 -

Examples 5 to 7

Different concentrates were prepared according to compositions listed in Table 2. In this table, HVI 60 refers to a paraffinic oil sold by Shell and NYNAS T22 to a naphthenic oil sold by Nynas. The ester of Example 3 is referred to as TMP C<sub>13</sub>; Synacto 3001 is an emulsifier commercially available from Exxon Chemical Limited being an oil solution of a mixture of salts of alkaryl sulphonic acids and salts of carboxylic acids of HLB approximately 10.8 and, in the formulations containing TMP C<sub>13</sub>, Synacto 3002 is a similar emulsifier but with HLB approximately 9.2; Emulsogen BLM is a commercial fatty amide. The concentrates were diluted with 25 parts of water to make milky emulsions which were tested in the Falex lubrication tester, according to ASTM D 3233, the test being modified to measure friction coefficient and temperature rise at a load below breaking value, 400 kg, during a time interval of 5 minutes, following the procedure of IP 241 Method D.

- 13 -

Table 2  
(The proportions are given in parts by weight.)

Example No.	(comparative)	5	6	7
HVI 60	--	--	51.0	10.0
NYNAS T22	81.0	71.0	--	--
TMP C <sub>13</sub>	--	10.0	30.0	64.8
Synacto 3001	16.0	15.0	12.8	9.0
Synacto 3002	--	1.0	3.2	13.5
Emulsogen BLM	3.0	3.0	3.0	2.7
<u>FALEX RESULTS</u>				
Friction Coefficient	0.134	0.122	0.107	0.094
Temperature Rise °C	44	41	35	29

The results show the significant increase in lubrication achieved by replacing increasing proportions of base oil by the ester.

#### Examples 8 to 11

To compare the esters according to the invention with known lubricity additives a standard formulation was prepared in the form of a microemulsion, the concentrate comprising, by weight percent, the components listed in Table 3. Synacto 2000 is a commercially available surfactant being an oil solution containing 50% by weight of salts of alkylaryl sulphonic acids with HLB of about 11, BDG is butyl diglycol. The corrosion inhibitor is an aqueous solution of alkanolamine salts of a mixture of tartaric and boric acids.

- 14 -

Table 3

Nynas T22	21.4
Synacto 2000	21.4
BDG	4.8
Corrosion Inhibitor	23.8
Water	23.8
Ester or Comparison	4.8

The concentrate was then mixed with water at a ratio of 1:25.

The materials used were as follows:

Comparison A : trimethylol propane (TMP) trioleate

Example 8 : TMP C<sub>11</sub>

Example 9 : TMP C<sub>13</sub>

Example 10 : PE C<sub>11</sub>

Example 11 : PE C<sub>13</sub>

A steel workpiece (steel designation 35 NCD 16) was ground with a grinding wheel (material designation 99 A60M6 V36) using the materials listed above as cutting fluid, and the ratio G of mass of material removed from the workpiece to that removed from the wheel was measured. The variation  $R_a$  in surface finish ( $R_a$  of the first piece,  $R_a$  of the 10th piece) in  $\mu\text{m}$ , from the workpiece, was also measured. The results are shown in Table 4.



- 15 -

Table 4

	G	R <sub>a</sub>
Comparison	191	0.35 to 0.46
Example 8	170	0.35 to 0.43
Example 9	196	0.38 to 0.43
Example 10	196	0.36 to 0.44
Example 11	157	0.37 to 0.43

These results show an improvement in the consistency of the finish using the esters of the invention over that of the comparison.

Examples 12 to 14

Using the same formulation as in Examples 8 to 11, the following Examples were used to test effectiveness of the esters according to the invention as components of cutting fluids in reaming of aluminium, under the following conditions: workpiece reference 5U 3Y 30; tool HSS.E at 5% cobalt; reaming of 750 holes; examination of the profile of every third hole by Perthometer M 3A; R<sub>a</sub> is the average in  $\mu\text{m}$  of these results.

The results are show in Table 5.

Table 5

		R <sub>a</sub>
Comparison A	TMP trioleate	2.3
Comparison B	Di(tridecyl) phthalate	3.2
Example 12	TMP C <sub>11</sub>	2.8
Example 13	TMP C <sub>13</sub>	2.35
Example 14	PE C <sub>11</sub>	2.6

- 16 -

These results show that the esters of the invention give significantly better performance than a diester in surface finish.

Examples 15 to 17

The procedure of Examples 5 to 7 was followed, to make emulsion concentrates as shown in Table 6. These were then diluted with 25 parts of water to give a micro-emulsion. Table 6 also shows the Falex results.

Table 6

Example No.	(comparative)	15	16	17
NYNAS T22	25.00	23.75	22.00	--
Corrosion Inhibitor	20.00	19.00	18.00	20.00
Synacto 3001	25.00	23.75	16.10	10.40
Synacto 3002	--	--	6.40	14.60
Water	30.00	28.50	27.00	25.00
TMP C <sub>13</sub>	--	5.00	10.00	30.00
<u>FALEX RESULTS</u>				
Friction Coefficient	0.115	0.105	0.100	0.092
Temperature Rise °C	37	33	29	27

The results show that, using the ester of the invention, there may be formulated a highly effective synthetic emulsion containing essentially no mineral oil (less than 1% mineral oil being brought into the concentrate from Synacto 3001 and 3002).

- 17 -

CLAIMS:

1. An ester of a C<sub>10</sub> to C<sub>15</sub> branched aliphatic carboxylic acid containing on average more than one branch per molecule in which no more than 20% of the branching is on the 2 carbon atom, and an aliphatic alcohol having at least three hydroxy groups.
2. An ester as claimed in claim 1, wherein the acid has been formed by the oxo process.
3. An ester as claimed in claim 1 or claim 2, derived from a C<sub>11</sub> acid.
4. An ester as claimed in claim 1 or claim 2, derived from a C<sub>13</sub> acid.
5. An ester as claimed in any of claims 1 to 4 in which the acid contains between 2 and 4 branches.
6. An ester as claimed in any of claims 1 to 5 in which the acid is a mixture of acids containing less than 40% by weight linear acid, and the content of acids branched on the 3 carbon and higher is equal to or higher than 40%.
7. An ester as claimed in any of claims 1 to 6 in which the aliphatic alcohol contains at least three primary hydroxy groups.
8. An ester as claimed in any one of claims 1 to 7 derived from trimethylol propane.
9. An ester as claimed in any one of claims 1 to 7 derived from pentaerythritol.
10. Trimethylol propane triundecanoate, the undecanoic acid being derived from a C<sub>11</sub> oxo process aldehyde.

- 18 -

11. Trimethylol propane tri-tridecanoate, the tridecanoic acid being derived from a C<sub>13</sub> oxo process aldehyde.

12. Pentaerythritol tetraundecanoate, the undecanoic acid being derived from a C<sub>11</sub> oxo process aldehyde.

13. Pentaerythritol tetra-tridecanoate, the tridecanoic acid being derived from a C<sub>13</sub> oxo process aldehyde.

14. A hydraulic fluid or lubricant comprising an ester as defined in any one of claims 1 to 13.

15. A cutting fluid comprising water, and emulsifying agent, and an ester as defined in any one of claims 1 to 13.

16. A cutting fluid as claimed in claim 15, which also comprises a mineral or synthetic oil.

17. A cutting fluid as claimed in claim 15, substantially free from mineral oil.

18. An emulsion concentrate comprising an ester as defined in any one of claims 1 to 13, an emulsifying agent, and water.

19. An emulsion concentrate as claimed in claim 18, wherein the ester represents up to 75% of the total weight of the components other than water.

20. An emulsion concentrate as claimed in claim 18, wherein the ester represents 2 to 70% of the total weight of the components other than water.

- 19 -

21. An emulsion concentrate as claimed in claim 18 wherein the ester represents 10 to 60% of the total weight of components other than water .

22. A method of metal working which uses as a lubricant or cutting fluid a composition as claimed in any one of claims 14 to 21.

23. The use of an ester as defined in any one of claims 1 to 13 as a lubricant aid in a cutting fluid.

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 91/00491

## I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) <sup>6</sup>

According to International Patent Classification (IPC) or to both National Classification and IPC

IPC<sup>5</sup>  
C 07 C 69/30; C 07 C 69/33

## II. FIELDS SEARCHED

Minimum Documentation Searched <sup>7</sup>

Classification System |

Classification Symbols

IPC<sup>5</sup>

C 07 C 69/00

Documentation Searched other than Minimum Documentation  
to the Extent that such Documents are Included in the Fields Searched <sup>8</sup>

## III. DOCUMENTS CONSIDERED TO BE RELEVANT <sup>9</sup>

Category <sup>10</sup>	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>
A	DE, A, 1594418 (ESSO) 3 September 1970 see pages 12-13; claims --	1
A	FR, A, 2254633 (INSTITUT FRANCAIS DU PETROLE) 11 July 1975 see pages 11-12; claims --	1
A	DE, A, 2336844 (UNILEVER EMERY) 31 January 1974 see pages 11-12; claims --	
A	DE, A, 2302918 (HENKEL) 25 July 1974 see pages 10-11; claims -----	1

<sup>10</sup> Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

## IV. CERTIFICATION

Date of the Actual Completion of the International Search

17th June 1991

Date of Mailing of this International Search Report

14. 08. 91

International Searching Authority

EUROPEAN PATENT OFFICE

Signature of Authorized Officer

*[Handwritten Signature]*

Mme Dagmar FRANK

**ANNEX TO THE INTERNATIONAL SEARCH REPORT  
ON INTERNATIONAL PATENT APPLICATION NO.**

GB 9100491  
SA 46163

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 31/07/91  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-A- 1594418	03-09-70	FR-A- 1430111 GB-A- 1028569 US-A- 3282971	
FR-A- 2254633	11-07-75	BE-A- 822831 CA-A- 1044216 DE-A- 2458441 GB-A- 1490707 NL-A- 7416151 US-A- 4061581	02-06-75 12-12-78 19-06-75 02-11-77 16-06-75 06-12-77
DE-A- 2336844	31-01-74	GB-A- 1441918 AT-B- 330327 BE-A- 802521 CH-A- 591556 FR-A,B 2196988 NL-A- 7309971	07-07-76 25-06-76 18-01-74 30-09-77 22-03-74 22-01-74
DE-A- 2302918	25-07-74	AT-B- 336154 AU-A- 6466774 BE-A- 809901 CA-A- 1042458 CH-A- 597139 FR-A,B 2214680 GB-A- 1444826 JP-C- 1260781 JP-A- 49109771 JP-B- 59028239 SE-B- 408793 US-A- 4053491 US-A- 4144183	25-04-77 24-07-75 18-07-74 14-11-78 31-03-78 19-08-74 04-08-76 25-04-85 18-10-74 11-07-84 09-07-79 11-10-77 13-03-79