

# PILOT-PLANT GASIFICATION OF PULVERIZED COAL WITH OXYGEN AND HIGHLY SUPERHEATED STEAM

by

G. R. Strimbeck,<sup>1/</sup> J. H. Holden,<sup>1/</sup> L. P. Rockenbach,<sup>2/</sup>  
J. B. Cordiner, Jr.,<sup>1/</sup> and L. D. Schmidt<sup>3/</sup>

## CONTENTS

	Page
Summary and conclusions.....	1
Introduction.....	1
Acknowledgments.....	2
Theoretical considerations affecting design of pilot plant, including a comparison of various coal-gasification systems.....	2
Mechanism of coal-particle gasification.....	4
Heat supply.....	5
Extent of reaction.....	6
Reactor design.....	7
Original design and flow sheets.....	7
Discussion of subsidiary problems involved.....	8
Description of pilot plant.....	10
Royster pebble stoves and superheated-steam flow sheet.....	10
Coal feeder and flow sheets.....	11
Generator construction.....	12
Dust train and flow sheet.....	12
Modifications of unit for runs 15-25.....	13
Modifications of unit for runs 26-31.....	13
Procedures used.....	13
Preliminary steam runs on Royster pebble stove.....	13
First gasifying runs.....	14
Superheated-steam runs (1-14).....	14
Low-temperature steam runs (15-25).....	16
Tests made using steam at 1,600°-2,000° F. (runs 26-31).....	17

<sup>1/</sup> Chemical engineer, Bureau of Mines, Morgantown, W. Va.

<sup>2/</sup> Gas engineer, Bureau of Mines, Morgantown, W. Va.

<sup>3/</sup> Chief, Synthesis Gas Production Branch, Bureau of Mines, Morgantown, W. Va.

## CONTENTS (Continued)

	<u>Page</u>
Results.....	18
Calculated results of gasification runs.....	18
Oxygen requirement.....	27
Slag distribution and generator brickwork condition..	27
Dust-removal and residue data.....	30
Data on sulfur content of gases.....	30
Accuracy of results.....	33
Discussion of results.....	35
Value of 2,900° F. steam for production of synthesis gas.....	37
Plans for future pilot-plant operations.....	38
Description of new apparatus and reasons for design..	38
Coal feeder.....	38
Roystor pebble stove.....	38
Generator.....	39
Dust-removal train.....	39
Projected experimental work.....	41

## TABLES

1. Calculated results on pilot-plant runs using high- temperature steam (runs 1-14).....	19
2. Calculated results on pilot-plant runs using low- temperature steam (runs 15A-25B).....	22
3. Calculated results on pilot-plant runs using inter- mediate-temperature steam (runs 26A-31B).....	25
4. Comparison of calculated with measured input of oxygen to the generator for each run.....	28
5. Percentage of total ash in coal remaining in generator as slag and percentage of total carbon gasified, based on residue measurement (runs 1-31).....	29
6. Weight distribution and chemical analyses of residues from pilot-plant runs 1-31.....	31
7. Screen analyses of coals used and residues collected for pilot-plant runs 1-31.....	32
8. Requirements per 1,000 S.C.F. of (CO + H <sub>2</sub> ) produced...	37

## ILLUSTRATIONS

<u>Fig.</u>	<u>Follows</u> <u>page</u>
1. Calculated steam requirement for gasification of standard Sewickley coal, using no oxygen.....	4
2. Calculated effect of steam:coal ratio on oxygen requirement for gasification of standard Sewickley coal.....	4
3. Calculated effect of entering steam temperature on oxygen requirement for gasification of standard Sewickley coal.....	6
4. Calculated effect of exit-gas temperature, °F., on oxygen requirement.....	6
5. Calculated effect of heat loss on oxygen requirement.....	6
6. Flow sheet for superheated-steam process.....	10
7. Arrangement of Royster pebble stoves in relation to generator.....	10
8. Close-up view of Royster pebble stove, showing valve arrangement for hand reversal.....	10
9. Royster pebble-stove design used in runs 1-14.....	10
10. Burner design used in Royster pebble stoves.....	10
11. Control instruments used in runs 1-31.....	10
12. Construction of refractory valves used in Royster pebble stove steam-exit lines.....	10
13. Flow sheet for pneumatic coal feeder.....	10
14. Pneumatic coal feeder; small vertical cylinder in right rear is continuous feeder.....	10
15. Schematic diagram of pneumatic coal-feeder control system.....	10
16. Refractory detail of gas generator.....	12
17. Diagram showing location of generator openings.....	12
18. Dust-removal train used in runs 1-31.....	12
19. View of dust-removal train; generator outlet at right.....	12
20. View of steam superheater used in runs 26-31.....	12
21. Refractory detail of steam superheater used in runs 26-31.....	12
22. Temperature distribution in generator for runs 1-14.....	16
23. Temperature distribution in generator for runs 15-25.....	16
24. Temperature distribution in generator for runs 26-31.....	16
25. Typical slag distribution in gas generator.....	26
26. A, Steam inlet from stove "A" before firing generator, May 1948; B, steam inlet from stove "A", showing slag attack, May 1949.....	28
27. A, Sight-hole tube before firing generator, May 1948; B, sight-hole tube, showing slag attack, May 1949.....	28

ILLUSTRATIONS (Continued)

<u>Fig.</u>	<u>Follows page</u>
28. A, Inside generator looking up to outlet before firing, May 1948; B, inside generator looking up to outlet, showing slag on walls, May 1949...	28
29. Coal-inlet tube with water-cooled nozzle inserted, showing slag attack, September 1949.....	28
30. A, Typical slag formation on generator wall, May 1949; B, typical slag formation on generator wall, September 1949.....	28
31. A, Steam inlet from stove "A", showing slag attack, September 1949; B, steam inlet from stove "B", showing slag attack, September 1949..	28
32. A, Coal-feed tube C, January 1950; B, coal-feed tube D, January 1950.....	28
33. A, Steam inlet from stove "A", January 1950 after cleaning away slag and damaged tube; B, thermo-couple tube E, January 1950.....	28
34. Plot of percentage of total ash remaining in generator against percentage of total carbon gasified.....	28
35. Volume of synthesis gas as measured by gas meter compared with that of carbon balance.....	28
36. Heat loss determined by heat balance compared with that determined by conduction through wall plus heat stored in wall.....	32
37. Effect of ratio of oxygen:coal on percentage of carbon gasified for runs 15-25.....	32
38. Effect of ratio of (oxygen + oxygen content of steam):coal on percentage of carbon gasified for runs 1-14.....	34
39. Effect of steam temperature on oxygen requirement for gasification of Sewickley coal at steam:coal ratio of 2.5.....	34
40. Effect of steam temperature on oxygen requirement for gasification of Sewickley coal at steam:coal ratio of 3.0.....	36
41. Effect of steam:coal ratio on oxygen requirement for low-temperature steam runs.....	36
42. Effect of steam:coal ratio on steam decomposition.....	36
43. Effect of steam:coal ratio on the percentage of carbon dioxide in dry synthesis gas.....	36
44. Effect of steam:coal ratio on hydrogen:carbon monoxide ratio.....	36
45. Value of steam at 2,900° F. for production of synthesis gas.....	36
46. Flow sheet for preparation of highly superheated steam.....	36
47. Flow sheet of dust-removal and cooling system.....	38
	38

ILLUSTRATIONS (Continued)

Fig.		Follows page
48.	New Royster pebble-stove refractory detail.....	38
49.	New Royster pebble-stove refractory detail; cross section.....	38
50.	Selas burner for Royster pebble stove.....	38
51.	Water-cooled valve for use in steam lines from stoves to gas generator.....	38
52.	Continuous slag-tap device for gas generator.....	38
53.	Construction detail of fogging chamber.....	40
54.	Construction detail of sludge-collecting tank.....	40
55.	Construction detail of moving-bed coke filter.....	40