

Bureau of Mines
Report of Investigations 5030



GASIFICATION OF PULVERIZED COAL WITH STEAM AND OXYGEN AT ATMOSPHERIC PRESSURE

BY G. R. STRIMBECK, J. B. CORDINER, JR., N. L. BAKER,
J. H. HOLDEN, K. D. PLANTS, AND L. D. SCHMIDT

United States Department of the Interior—February 1954

LIBRARY
LOUISIANA STATE UNIVERSITY

GASIFICATION OF PULVERIZED COAL WITH STEAM AND OXYGEN AT ATMOSPHERIC PRESSURE

BY G. R. STRIMBECK, J. B. CORDINER, JR., N. L. BAKER,
J. H. HOLDEN, K. D. PLANTS, AND L. D. SCHMIDT

* * * * * * * * * * * * * Report of Investigations 5030



UNITED STATES DEPARTMENT OF THE INTERIOR

Douglas McKay, Secretary

BUREAU OF MINES

J. J. Forbes, Director

Work on manuscript completed June 1953. The Bureau of Mines will welcome reprinting of this paper, provided the following footnote acknowledgment is made: "Reprinted from Bureau of Mines Report of Investigations 5030."

The work upon which this report is based was done under a cooperative agreement between the Bureau of Mines, United States Department of the Interior, and West Virginia University.

GASIFICATION OF PULVERIZED COAL WITH STEAM AND OXYGEN
AT ATMOSPHERIC PRESSURE

by

G. R. Strimbeck,^{1/} J. B. Cordiner, Jr.,^{2/} N. L. Baker,^{2/} J. H. Holden,^{2/}
K. D. Plants,^{2/} and L. D. Schmidt^{3/}

CONTENTS

| | Page |
|---|------|
| Summary and conclusions | 1 |
| Introduction | 2 |
| Acknowledgments | 2 |
| Design of gasifier and its effect on experimental program | 2 |
| Description of pilot plant | 4 |
| Reactant and product flows | 4 |
| Gasifier construction details | 5 |
| Slag-removal equipment | 5 |
| Primary reaction zone | 5 |
| Secondary reaction zone | 6 |
| Heat trap or cooling zone | 6 |
| Modifications in gasifier construction | 6 |
| Reactant-injection-burner designs | 7 |
| Coal-feeding system | 10 |
| Dust-removal and gas-cooling equipment | 11 |
| Test procedures used | 12 |
| Operability of plant | 13 |
| Methods of measuring reactant and product quantities | 14 |
| Stability of refractory linings | 14 |
| Results | 16 |
| Principal results | 16 |
| Coals charged | 24 |
| Types of residues recovered | 26 |
| Moisture tests and steam-decomposition results | 26 |
| Data on sulfur content of gas | 28 |
| Data on dust content of gas | 29 |
| Reactant-injection-burner-design data | 30 |
| Accuracy of results | 32 |
| Probable accuracy of measurements | 32 |
| Product-gas measurements | 32 |
| Residue measurements | 32 |
| Comparison of product-gas data and residue data | 33 |
| Other measurements | 33 |
| Discussion of results | 34 |
| Effect of oxygen-carbon ratio | 34 |
| Effect of steam-carbon ratio | 35 |
| Process heat balance | 35 |
| Process cost evaluation | 36 |
| Development of experimental program | 37 |

^{1/} Supervising engineer, Bureau of Mines, Morgantown, W. Va.

^{2/} Chemical engineer, Bureau of Mines, Morgantown, W. Va.

^{3/} Chief, Synthesis Gas Branch, Bureau of Mines, Morgantown, W. Va.

TABLES

| | Page |
|---|------|
| 1. Principal results on pilot-plant atmospheric gasifier 4, runs 4 through 34 | 17 |
| 2. Ultimate analyses, calorific values, and ash fusibilities of Sewickley-bed coal used for runs 1 through 34 on atmospheric gasifier 4 | 25 |
| 3. Weights, analyses, and calorific values of residues recovered .. | 26 |
| 4. Comparison of experimentally determined moisture content of product gas with values calculated from flow and residue data. | 28 |
| 5. Sulfur content of coal and H ₂ S and organic sulfur contents of product gas for runs 13 through 20 and 30 through 34 | 29 |
| 6. Dust concentration leaving scrubber for test runs on atmospheric gasifier 4 | 30 |
| 7. Reactant-injection-burner design data | 31 |

ILLUSTRATIONS

| <u>Fig.</u> | <u>Follows</u> |
|---|----------------|
| | <u>page</u> |
| 1. Pilot-plant flowsheet for atmospheric pressure gasification . | 4 |
| 2. Atmospheric pressure gasifier 4, design 1 | 4 |
| 3. Atmospheric pressure gasifier 4, design 2 | 6 |
| 4. Atmospheric pressure gasifier 4, design 3 | 6 |
| 5. Atmospheric pressure gasifier 4, design 4 | 6 |
| 6. Reactant injection burner for gasifier 4, design 1 | 6 |
| 7. Atmospheric gasifier 4 char formation obtained using burner design 1 | 8 |
| 8. Reactant injection burner for gasifier 4, design 3 | 8 |
| 9. Reactant injection burner for gasifier 4, design 4 | 8 |
| 10. Reactant injection burner for gasifier 4, design 5 | 8 |
| 11. Reactant injection burner for gasifier 4, design 6 | 8 |
| 12. Reactant injection burner for gasifier 4, design 7 | 8 |
| 13. Reactant injection burner for gasifier 4, design 9 | 10 |
| 14. Coal handling flowsheet for atmospheric gasifier 4 | 10 |
| 15. Atmospheric pressure gasifier 4; primary reaction zone after run 34 | 14 |
| 16. Slag tap and primary zone after run 34 | 16 |
| 17. View of primary zone looking toward point of entry of A burner, after run 34 | 16 |
| 18. View of primary zone looking toward point of entry of B burner, after run 34 | 16 |
| 19. Throat between primary and secondary zones, showing ends of reactant-injection burners after run 34 | 16 |
| 20. Fly ash deposits on platen coils - thermocouple 13 at side - after run 34 | 16 |
| 21. Effect of oxygen-carbon ratio on residue and slag distribution | 16 |
| 22. Comparison of carbon gasified from flow and residue data .. | 26 |
| 23. Effect of reactant ratios on carbon gasified | 32 |
| 24. Effect of reactant ratios on carbon requirement | 34 |
| 25. Effect of reactant ratios on oxygen requirement | 34 |
| 26. Effect of steam-carbon ratio on CO ₂ content of product gas .. | 34 |
| 27. Effect of reactant ratios on H ₂ -CO ratio in product gas .. | 34 |
| 28. Effect of steam-carbon ratio on steam decomposition | 34 |
| 29. Heat-flow distribution; atmospheric gasifier 4 | 34 |
| 30. Heat-flow distribution; standard blue-gas set | 34 |
| 31. Nomograph for determining reactants costs per M std. c.f. of (CO + H ₂) | 34 |
| | 36 |