FOSSIL

DEVELOPMENT OF ALCOHOL-BASED SYNTHETIC TRANSPORTATION FUELS FROM COAL-DERIVED SYNTHESIS GASES

Final Technical Report for September 1979-July 1982

December 15, 1982

Work Performed Under Contract No. AC22-79ET14858

Chem Systems Inc. Research and Development Group Fairfield, New Jersey





U.S. DEPARTMENT OF ENERGY

REPRODUCED BY
NATIONAL TECHNICAL
INFORMATION SERVICE
U.S. DEPARIMENT OF COMMERCE
SPRINGFIELD, VA. 22161

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof."

This report has been reproduced directly from the best available copy.

多一次 人名英格兰 医多种 医多种 医多种

Available from the National Technical Information Service, U. S. Department of Commerce, Springfield, Virginia 22161.

Price: Printed Copy A16 Microfiche A01

Codes are used for pricing all publications. The code is determined by the number of pages in the publication. Information pertaining to the pricing codes can be found in the current issues of the following publications, which are generally available in most libraries: Energy Research Abstracts, (ERA); Government Reports Announcements and Index (GRA and I), Scientific and Technical Abstract Reports (STAR); and publication, NTIS-PR-360 available from (NTIS) at the above address.

FINAL TECHNICAL REPORT

SEPTEMBER, 1979 - JULY, 1982

DEVELOPMENT OF ALCOHOL-BASED SYNTHETIC TRANSPORTATION FUELS FROM COAL-DERIVED SYNTHESIS GASES

CONTRACT NO. DE-AC 22-79. ET 14858

SUBMITTED TO:

U.S. DEPARTMENT OF ENERGY COAL LIQUEFACTION PROJECT MANAGEMENT PITTSBURGH ENERGY TECHNOLOGY CENTER PITTSBURGH, PA 15213

PREPARED BY:

CHEM SYSTEMS INC.
RESEARCH AND DEVELOPMENT GROUP
ONE EVANS STREET
FAIRFIELD, NEW JERSEY 07006

DOE Project Manager: Richard Diffenbach Chem Systems Project Manager: Marvin I. Greene

DECEMBER 15, 1982

TABLE OF CONTENTS

		PAGE
1.	AB STRACT	1
11.	EXECUTIVE SUMMARY A. Summary of Accomplishments B. Conclusions C. Recommendations	2 2 3 5
III.	BACKGROUND AND PROGRAM DESCRIPTION	8
IV.	EXPERIMENTAL APPARATUS AND PROCEDURES A. Plug-Flow, Vapor-Phase Reaction System B. Berty Gradientless Reaction System C. Slurry-Phase Autoclave Reaction System D. Analytical Procedures E. Catalyst Activation Procedures	12 12 15 18 19 28
۷.	& SCREENING STUDIES (TASK 1) A. Literature Review 1. Review of Early Catalyst Development 2. Recent Literature Review 3. Review of Chemical Mechanisms 4. Schulz-Flory Distribution 5. Other Considerations B. Catalyst Preparation Procedures 1. Classification of Catalyst Types 2. Preparation Methods a. Evaporation b. Coprecipitation c. Impregnation d. Detergent Dispersion e. Cobalt Carbonyl Impregnation f. Mechanical Blending	31 31 33 39 45 49 50 50 50 50 62 62 65 67
	g. Proprietary Catalysts C. Experimental Results 1. Calculation Procedures	67 67 73
	 Detailed Run Summaries Analysis of Results Overview Screening Studies Using Proprietary Catalysts Screening Studies With In-House Formulations 	73 73 74 81

TABLE OF CONTENTS

		PAGE
VI.	A. Overview B. Process Variables Studies in Vapor-Phase Reactor Systems 1. UCI L-1122 Catalyst a. Analysis of 292 Hour Campaign With Freshly Reduced Catalyst b. Analysis of Second Campaign With Re-reduced Catalyst 2. UCI L-1123 Catalyst 3. UCI L-1124 Catalyst C. Process Variables Studies in Slurry-Phase Reactor Systems 1. Tests With n-Heptadecane Slurry Oil	95 96 98 114 131 139 150 163 164
VII.	2. Tests With Witco 40 Slurry 0il DISCUSSION OF RESULTS OF CATALYST PERFORMANCE STUDIES (IASK 4)	179 197
VIII.	DISCUSSION OF RESULTS OF ENGINEERING & ECONOMIC STUDIES (TASK 3) A. Overview B. Conceptual Design of an ALKANOLS For Syn Gas Plant 1. Design Basis 2. Process Description 3. Cost of Production Estimates 4. Sensitivities of Process Parameters 5. Comparative Economics of ALKANOLS vs. Methanol & Mobil MTG Gasoline C. Utilization of ALKANOL Fuels 1. Properties of ALKANOL Fuels 2. Economics of Use of ALKANOLS as Gasoline Blending Stocks	199 201 201 207 212 213 221 224 228 235
IX.	INVENTION DISCLOSURES	242
х.	TECHNICAL PAPERS	243
XI.	REFERENCES	244
XII.	ACK NO WLEDGEMENTS	249
XIII.	APPENDIX A. Catalyst Classification of Catalyst Compositions B. Computerized Run Sheets For Catalyst Screening Studies	251

LIST OF TABLES

Table No.	<u> Title</u>	<u>Page No.</u>
II-l	Outline of Tasks For Optional Development Programs	6-7
V-1	Typical Alcohol Product Distribution	35
V-2"	Comparison of Stoichiometry and Thermodynamics of Synthesis Gas Conversion Processes	51
V-3	Summary of Catalysts Prepared By Evaporation	54~56
V-4	Summary of Catalysts Prepared by Coprecipitation	59-60
V-5	Comparison of Calculated Vs. Measured Compositions of Coprecipitated Catalysts	61
V-6	Summary of Catalysts Prepared By Impregnation On To Inert Supports	63
V- 7	Summary of Catalysts Prepared By Impregnation of Metal On To Existing Catalysts	64
V-8	Summary of Catalysts Prepared By Cobalt Carbonyl Impregnation	66
٧-9	Screening Results With Highest ALKANOLS Selectivities Observed For Each Group Of In-House Catalyst Formulations	75
V-1 0	Comparison of Initial Catalyst Performance Of UCI Catalysts L-1122, L-1123, and L-1124	76
y - 11	Initial Catalyst Performance of UCI L-1122 Catalyst Screened in the Berty Reactor	77
V - 1 2	Initial Catalyst Performance of UCI L-1723 Catalyst Screened in the Diluted-Bed, Plug-Flow Reactor	79
V-13	Initial Catalyst Performance of UCI L-1124 Catalyst Screened in the Berty Reactor	82
V-14	Summary of Studies With 5 or 6 Component Catalyst Systems (Group I)	83-86
V-15	Summary of Studies With Quarternary Catalyst Systems (Group II)	88-89
V-16	Summary of Studies With Ternary Catalyst Systems (Group III)	90

LIST OF TABLES

Table No.	<u>Title</u>	Page No.
V-17	Summary of Studies With Binary Catalyst Systems (Group IV)	91
V-18	Summary of Studies With Modified Low Pressure, Methanol Synthesis Catalysts (Group V)	92-93
VI-İ	Comparison of Catalyst Performance Under Longer-Term Testing	97
VI -2	Summary For Run #213-74B	99-103
VI-3	Summary For Run #213-74-B-R	104-105
VI-4	Crude ALKANOL Fuel Weight Distribution (Run 213-74B)	106-110
VI-5	Crude ALKANOL Fuel Weight Distribution (Run 213-748-R)	111-112
VI -6	Carbon Monoxide Conversion For UCI L-1122 Catalyst During Test Campaigns in The Berty Reactor	113
V I -7	Synthesis Gas Compositions Studied During First 292-Hour Test Campaign With UCI L-1122 Catalyst in The Berty Reactor	115
VI-8	Summary For Run #213-66P	141-143
VI-9	Crude ALKANOL Fuel Weight Distribution (Run 213-66)	144-146
VI-10	Summary For Run #213-82B	151-15?
VI-11	Crude ALKANOL Fuel Weight Distribution (Run 213-82)	153-154
VI-12	Effect of Carbon Dioxide Content of 2/1 Hydrogen/ Carbon Monoxide Synthesis Gases on L-1124 Catalyst Performance	157
VI-13	Summary For Run #226-28\$	166-167
VI-14	Crude ALKANOL Fuel Weight Distribution (Run 226-28S)	168-169
VI-15	Physical Properties of Witco 40 Mineral Oil	180
VI-16	Summary For Run #226-42S	184-185

LIST OF TABLES

Table No.	<u>Title</u>	Page No.
VI-17	Crude ALKANOL Fuel Weight Distribution (Run 226-42S)	186-187
VI-18	Effect of Carbon Dioxide Partial Pressure on L-1122 Catalyst Activity in Slurry Autoclave	189
VIII-1	Carbon Number Distribution For Assumed Product Slate	203
VIII-2	Material Balance For Conceptual Plant Design	208
VIII-3	Utility Summary For Base Case Estimate	214
VIII-4	Inside Battery Limits Capital Costs For Base Case Estimate	215
VIII-5	Total Installed Capital Cost Summary For Base Case Estimate	216
VIII-6	Estimated Cost of Production (Excl. Syn Gas) For Base Case Design	217
VIII-7	Sensitivity Analysis For ALKANOLS Production	218
VIII-8	Mobil MTG Process Plant Investment and Production Cost Estimates	223
VIII-9	Effect of Synthesis Loop Capacity	222
VIII-10	Plant and Production Costs (Excl. Syn Gas) For Methyl Fuel From Syn Gas	225
VIII-11	Impact of Synthesis Gas Costs on Three Indirect Liquefaction Processes	226
VIII-12	Properties of ALKANOL Mixtures	228
VIII-13	Effect of ALKANOLS Addition on Alcohols Solubility in 10% Alcohol/90% Gasoline Blends	232
VIII-14	Thermochemical Properties of 10% ALKANOL/ 90% Gasoline Blends	236
VIII-15	Estimated Octane Improvement Costs Gulf Coast Basis, 1985	238
VIII-16	Estimated Refining Values of Oxygenated Fuels at 5-10% Addition Rates to 88 RdON Unleaded Gasoline	239

Figure No.	Title	Page No.
IV-1	Schematic of Plug-Flow Diluted-Bed, Vapor-Phase Reaction System	13
IV-2	Schematic of Plug-Flow Diluted-Bed, Vapor-Phase Reactor	14
IV-3	Schematic of Liquid and Gaseous Feed Systems For Berty Reactor	16
IV-4	Schematic of Berty Reactor	17
IV-5	Schematic of Slurry-Phase Autoclave Reaction System	20
IV-6	Sample Chromatogram For Analysis of Condensed Aqueous Alcohol Phase	23
I V- 7	Gas Chromatographic System For Analysis of Berty Reactor Effluent Stream	27
I Y-8	Sample Chromatogram and Integration For Vapor- Phase Analysis of ALKANOLS Synthesis Products	29
V-1	IFP's C1-C5 Alcohols From Synthesis Gas Process	36
V-2	Reactions of Carbon Monoxide and Hydrogen	40
V-3	Temperature Programming of Calcining Oven	52
V-4	Crude ALKANOL Fuel Weight Distribution Vs. Reactor Temperature	80
VI-1	Corrected CO Conversion Vs. Hours On Stream For UCI L-1122 Catalyst in Berty Reactor	117
VI-2	Space Time Yield to ALKANOLS Vs. On-Stream Time For UCI L-1122 Catalyst	118
VI -3	CO Conversion to ALKANOLS Vs. On-Stream Time For UCI L-1122 Catalyst in Berty Reactor	119
VI-4	Methanol Content of ALKANOLS Vs. On-Stream Time For UCI L-1122 Catalyst	120
V I -5	C ₂ -C ₆ Oxygenates Content of ALKANOLS Vs. On-Stream Time For UCI L-1122 Catalyst	121
VI-6	C4-Cg Hydrocarbon Content of ALKANOLS Vs.	122

Figure No.	<u>Title</u>	Page No.
VI-7	Schulz-Flory Product Distribution	124
VI-8	Modified Schulz-Flory Probability Parameter Vs. On-Stream Time For UCI L-1122 Catalyst Tested in the Berty Reactor	125
VI-9	Typical ALKANOLS Synthesis Product Distribution For UCI L-1122 Catalyst	126
VI-10	Corrected CO Conversion Vs. On-Stream Time For UCI L-1122 Catalyst	. 128
VI-11	Corrected CO Conversion Vs. H2/CO Molar Ratio in Synthesis Gas For UCI L-1122 Catalyst	129
VI -12	Corrected CO Conversion Vs. CO ₂ Content of Synthesis Gas For UCI L-1122 Catalyst	130
VI-13	Effect of Space Velocity on CO Conversion For UCI L-1322 Catalyst	132
VI-14	Corrected CO Conversion Vs. Cumulative On-Stream Time For UCI L-1122 Catalyst	133
VI-15	ALKANOLS Selectivity Vs. Cumulative On-Stream Time For UCI L-122 Catalyst	135
VI-16	ALKANOLS Composition Vs. Cumulative On-Stream Time For UCI L-1122 Catalyst	136
VI-17	Modified Schulz-Flory Probability Parameter Vs. Cumulative On-Stream Time For UCI L-1122 Catalyst	137
VI-18	Carbon Number Distribution of Synthesis Products For UCI L-1122 After 590 Hours Cumulative On-Stream Time	138
VI-19	CO Conversion Vs. On-Stream Time For UCI L-1123 Catalyst	147
VI -20	Product Selectivity Vs. On-Stream Time For UCI L-1123 Catalyst	148
VI-27	Crude ALKANOL Distribution Vs. On-Stream Time For UCI L-1123 Catalyst	149
VI-22	Modified Schulz-Flory Probability Parameter Vs. On-Stream Time For UCI L-1123 Catalyst	155

Figure No.	<u>Title</u>	Page No.
VI-23	Synthesis Product Composition Vs. Carbon Number of Product For UCI L-1123 Catalyst	156
VI -24	CO Conversion Vs. On-Stream Time For UCI L-1124 Catalyst	158
VI-25	ALKANOLS Selectivity Vs. On-Stream Time For UCI L-1124 Catalyst	159
VI -26	Crude ALKANOL Composition Vs. On-Stream Time For UCI L-1124 Catalyst	160
VI-27	Schulz-Flory Probability Parameter Vs. On-Stream Time For UCI L-1124 Catalyst	161
VI -28	Synthesis Product Composition Vs. Carbon Number of Product For UCI L-1124 Catalyst in Berty Reactor	162
¥I - 29	Effect of On-Stream Time on CO Conversion For UCI L-1122 Catalyst in Slurry-Phase Autoclave Reaction System	171
VI -30	Apparent Effect of Space Velocity at Constant Pressure on CO Conversion For UCI L-1122 Catalyst	172
¥I-31	Effect of Reaction Pressure on CO Conversion For UCI L-1122 Catalyst in Slurry-Phase Autoclave Reaction System	174
VI-32	Effect of On-Stream Time on ALKANOLS Selectivity For UCI L-1122 Catalyst in the Slurry-Phase Autoclave Reaction System	. 175
VI -33	Effect of On-Stream Time on Methanol Content of ALKANOLAS For UCI L-1122 Catalyst	176
VI -34	Effect of On-Stream Time on C ₂ -C ₆ Oxygenates Content of ALKANOLS For UCI L-1122 Catalyst	177
VI-35	Effect of On-Stream Time on C4-C9 Hydrocarbon Content of ALKANOLS For UCI L-1122 Catalyst	178
VI -36	Modified Schulz-Flory Probability Parameter Vs. On-Stream Time For UCI L-1122 Catalyst in Slurry Autoclaye Reactor	181

Figure No.	<u>Title</u>	<u>Page No.</u>
VI-37	Synthesis Product Distribution By Carbon Number For UCI L-1122 Catalyst in Slurry Autoclave Reactor	182
VI -38	Effect of On-Stream Time on CO Conversion For UCI L-1122 Catalyst	190
VI -39	ALKANOLS Selectivity Vs. On-Stream Time For UCI L-1122 Catalyst in Slurry Autoclave Reaction System	191
VI -40	Methanol Content of Crude ALKANOLS Vs. On-Stream Time For UCI L-1122 Catalyst	192
VI-41	C ₂ -C ₆ Oxygenates Content of Crude ALKANOLS Vs. On-Stream Time For UCI L-1122 Catalyst	194
VI <i>-</i> 42	C4-C9 Hydrocarbon Content of Crude ALKANOLS Vs. On-Stream Time For UCI L-1122 Catalyst	195
VI -43	Synthesis Product Distribution Vs. Carbon Number For UCI L-1122 Catalyst	196
VIII-1	Conceptual ALKANOLS Synthesis Loop	209
VI II-2	Conceptual ALKANOLS Porduct Dehydration Section	210
VI II-3	Sensitivity of ALKANOLS Production Costs to Key Process Parameters	220
V111-4	Synfuel Product Cost Vs. Synthesis Gas Cost	. 227
VI II-5	Effect of ALKANGLS Composition on Increase in Gasoline Reid Vapor Pressure (RVP) as a Function of ALKANGLS Content in Gasoline	230
VIII-6	Effect of C ₂ -C ₄ Alcohol Content of Alcohol (15-18%) / Gasoline (82-85%) Blends on Gasoline Driveability	233
VIII-7	Water Tolerance of 13% ALKANOL/87%	234