

LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page</u>
III-1	Summary of bubble-column hydrodynamic studies	12
IV-1	Criteria for distributor design (evaluated at $u_g=0.01$ m/s)	22
V-1	Comparison between parameters used for bubble diameter measurements (FT-300 wax, 265°C, 0.051 m ID column, 1.85 mm orifice plate distributor)	144
V-2	Effect of "weeping" on small bubble diameter obtained by DGD (FT-300 wax, Run 13-3, 265°C, 0.051 m ID column, 1.85 mm orifice plate distributor)	209
VI-1	Physical properties of waxes	219
VI-2	Range of values for various parameters used in the correlations	226
VI-3	Goodness of fit and parameters for hold-up correlations based on dimensionless groups (using data for all waxes; ϵ_g - %)	230
VI-4	Goodness of fit and parameters for empirical hold-up correlations (using data for all waxes; ϵ_g - %)	232
VI-5	Goodness of fit and parameters for hold-up correlations from literature (using data for all waxes; ϵ_g - %)	233
VI-6	Goodness of fit and parameters for area correlations - FT-300 wax (a - m^{-1})	245
VI-7	Goodness of fit and parameters for area correlations - Sasol's Arge wax and Mobil reactor wax (a - m^{-1})	247
A-1	Summary of experiments performed in the small bubble columns (0.051 m ID)	267
A-2	Summary of experiments performed in the large bubble columns (0.229 - 0.241 m ID)	271
D-1	Summary of dynamic gas disengagement results for FT-300 wax (Run 13-3, 0.051 m ID column, 1.85 mm orifice plate distributor, 265°C)	294

LIST OF TABLES (contd.)

<u>Table</u>	<u>Title</u>	<u>Page</u>
D-2	Summary of dynamic gas disengagement results for FT-300 wax (Run 13-2, 0.051 m ID column, 1.85 mm orifice plate distributor, 200°C)	295
D-3	Summary of dynamic gas disengagement results for FT-300 wax (Run 6-2, 0.051 m ID column, 4 mm orifice plate distributor, 265°C)	296
D-4	Summary of dynamic gas disengagement results for FT-300 wax (Run 2-8, 0.229 m ID column, 19 X 1.85 mm perforated plate distributor, 265°C)	297
D-5	Summary of dynamic gas disengagement results for Sasol's Arge wax (Run 8-4, 0.051 m ID column, 1.85 mm orifice plate distributor, 265°C)	298
D-6	Summary of dynamic gas disengagement results for Mobil's reactor wax (Run 9-3, 0.051 m ID column, 1.85 mm orifice plate distributor, 265°C)	299

LIST OF FIGURES

<u>Figure</u>	<u>Title</u>	<u>Page</u>
IV-1	19 X 1.85 mm perforated plate distributor	25
IV-2	30 X 1.5 mm perforated pipe distributor	26
IV-3	Flow diagram of experimental apparatus	28
V-1	Bubble column flow regime map	31
V-2	Effect of superficial gas velocity on the flow regime for FT-300 wax at 265°C in the 0.051 m ID column using the 4 mm orifice plate distributor (photographs)	34
V-3	Effect of distributor type on the flow regime for FT-300 wax at 265°C in the 0.051 m ID column - 40 μ m SMP vs. 4 mm orifice plate distributor (photographs)	36
V-4	Effect of distributor type on the flow regime for FT-300 wax at 265°C in the 0.051 m ID column - 40 μ m SMP vs. 1.85 mm orifice plate distributor (photographs)	37
V-5	Effect of distributor type on foam produced with FT-300 wax at 265°C in the 0.051 m ID column (photographs)	39
V-6	Effect of height above the distributor on the flow regime for FT-300 wax at 265°C in the 0.051 m ID column using the 1.85 mm orifice plate distributor (photographs)	41
V-7	Effect of superficial gas velocity and liquid medium on slug frequency at 265°C for the 1.85 mm orifice plate distributor in the 0.051 m ID column	42
V-8	Effect of superficial gas velocity and liquid medium on slug frequency at 265°C for the 40 μ m SMP distributor in the 0.051 m ID column	44
V-9	Effect of radial position and superficial gas velocity on the flow regime for FT-300 wax at 265°C using the 19X1.85 mm distributor in the 0.229 m and 0.241 m ID columns (photographs)	47
V-10	Effect of start-up procedure and superficial gas velocity on gas hold-up for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor	52

LIST OF FIGURES (contd.)

<u>Figure</u>	<u>Title</u>	<u>Page</u>
V-11	Effect of operating procedure and superficial gas velocity on gas hold-up for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor	54
V-12	Effect of start-up procedure and superficial gas velocity on gas hold-up for FT-300 wax at 265°C in the 0.051 m ID column with the 40 μ m SMP distributor	56
V-13	Effect of operating procedure and superficial gas velocity on gas hold-up for FT-300 wax at 265°C in the 0.229 m ID column with the 19 X 1.85 mm perforated plate distributor	57
V-14	Effect of wax aging on gas hold-up for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor	61
V-15	Effect of wax aging on gas hold-up for FT-300 wax at 265°C in the 0.229 m ID column with the 19 X 1.85 mm perforated plate distributor	62
V-16	Effect of run history and superficial gas velocity on gas hold-up for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor	64
V-17	Results from long term stability studies with FT-300 wax at 265°C and comparison with average values from other runs in the 0.051 m ID column with the 1.85 mm orifice plate distributor	66
V-18	Effect of operating temperature on gas hold-up for FT-300 wax in the 0.051 m ID column with the 1.85 mm orifice plate distributor	70
V-19	Effect of operating temperature on gas hold-up for FT-300 wax in the 0.051 m ID column with the 40 μ m SMP distributor	71
V-20	Effect of operating temperature on gas hold-up for FT-300 wax in the 0.229 m ID column with the 19 X 1.85 mm perforated plate distributor	73
V-21	Effect of operating temperature on gas hold-up for FT-300 wax in the 0.229 m ID column with the 5 X 1 mm perforated plate distributor, and comparison with literature	75
V-22	Effect of column diameter on gas hold-up for FT-300 wax at 265°C with the 1.85 mm distributor in the 0.051 m ID column and the 19 X 1.85 mm distributor in the 0.229 m ID column	79

LIST OF FIGURES (contd.)

<u>Figure</u>	<u>Title</u>	<u>Page</u>
V-23	Effect of column diameter on gas hold-up for FT-300 wax at 265°C with the 1.85 mm distributor in the 0.051 m ID column and the 19 X 1.85 mm distributor in the 0.229 m ID column	81
V-24	Effect of column diameter on gas hold-up for FT-300 wax at 265°C with the 1 mm distributor in the 0.051 m ID column and the 19 X 1 mm distributor in the 0.229 m ID column	82
V-25	Effect of column diameter on gas hold-up for Sasol's Arge reactor wax at 265°C with the 1.85 mm distributor in the 0.051 m ID column and the 19 X 1.85 mm distributor in the 0.229 m ID column	84
V-26	Effect of distributor type on gas hold-up for FT-300 wax at 265°C in the 0.051 m ID column	87
V-27	Effect of distributor type on gas hold-up for FT-300 wax at 265°C in the 0.229 m ID column	89
V-28	Effect of distributor type on gas hold-up for FT-200 wax at 265°C in the 0.051 m ID column	91
V-29	Effect of oxygenates on gas hold-up for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor	94
V-30	Effect of oxygenates on gas hold-up for FT-300 wax at 265°C in the 0.051 m ID column with the 40 μ m SMP distributor	96
V-31	Effect of superficial gas velocity, distributor type and temperature on gas hold-up for Sasol's Arge reactor wax in the 0.051 m ID column	99
V-32	Effect of superficial gas velocity, distributor type and temperature on gas hold-up for Mobil's reactor wax in the 0.051 m ID column (composite from Mobil's runs CT-256-9, -11 and -12)	101
V-33	Effect of superficial gas velocity, start-up procedure and distributor type on gas hold-up for distilled water in the 0.051 m ID column	103
V-34	Effect of liquid medium and superficial gas velocity on gas hold-up in the 0.051 m ID column with the 1.85 mm orifice plate distributor	105

LIST OF FIGURES (contd.)

<u>Figure</u>	<u>Title</u>	<u>Page</u>
V-35	Effect of liquid medium and superficial gas velocity on gas hold-up in the 0.051 m ID column with the 40 μ m SMP distributor	106
V-36	Effect of liquid medium and superficial gas velocity on gas hold-up at 265°C in the 0.051 m ID column with the 1 mm orifice plate distributor	108
V-37	Comparison of gas hold-ups obtained in studies with sintered metal plate distributors	111
V-38	Comparison of gas hold-ups obtained in studies with perforated plate distributors	115
V-39	Schematic diagram of axial gas hold-up apparatus	118
V-40	Effect of superficial gas velocity and height above the distributor on axial gas hold-up for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor	121
V-41	Effect of superficial gas velocity and height above the distributor on axial gas hold-up for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor	123
V-42	Effect of superficial gas velocity on gas hold-up for FT-300 wax at 265°C in the 0.051 m ID stainless steel and glass columns with a 1.85 mm orifice plate distributor	125
V-43	Effect of superficial gas velocity and height above the distributor on axial gas hold-up for FT-300 wax at 265°C in the 0.051 m ID column with the 40 μ m SMP distributor	126
V-44	Effect of superficial gas velocity and height above the distributor on axial gas hold-up for FT-300 wax at 265°C in the 0.229 m ID column with the 19 X 1.85 mm perforated plate distributor	128
V-45	Effect of superficial gas velocity on gas hold-up for FT-300 wax at 265°C in the 0.241 m ID stainless steel and 0.229 m ID glass columns with the 19 X 1.85 mm perforated plate distributor	129
V-46	Effect of superficial gas velocity and height above the distributor on axial gas hold-up for Sasol's Arge reactor wax at 265°C in the 0.229 m ID column with the 19 X 1.85 mm perforated plate distributor	131

LIST OF FIGURES (contd.)

<u>Figure</u>	<u>Title</u>	<u>Page</u>
V-47	Effect of superficial gas velocity on gas hold-up for Sasol's Arge reactor wax at 265°C in the 0.241 m ID stainless steel and 0.229 m ID glass columns with a 19 X 1.85 mm perforated plate distributor	132
V-48	image processing system	138
V-49	Viewing port in the 0.241 m ID stainless steel column	147
V-50	Effect of superficial gas velocity and height above the distributor on the Sauter mean bubble diameter for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor (by photography)	149
V-51	Effect of height above the distributor on the bubble size distribution for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor (by photography)	150
V-52	Effect of superficial gas velocity and height above the distributor on the Sauter mean bubble diameter for FT-300 wax at 265°C in the 0.229 m ID column with a 19 X 1.85 mm perforated plate distributor (by photography)	152
V-53	Effect of flow regime on the bubble size distribution for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor (by photography)	156
V-54	Effect of flow regime on the bubble size distribution for FT-300 wax at 265°C in the 0.051 m ID column with the 40 μm SMP distributor (by photography)	157
V-55	Effect of flow regime on the bubble size distribution for FT-300 wax at 265°C in the 0.229 m ID column with the 19 X 1.85 mm perforated plate distributor (by photography)	159
V-56	Effect of superficial gas velocity on the Sauter mean bubble diameter for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor (by photography)	161
V-57	Effect of superficial gas velocity on the Sauter mean bubble diameter for FT-300 wax at 265°C in the 0.051 m ID column with the 40 μm SMP distributor (by photography)	162

LIST OF FIGURES (contd.)

<u>Figure</u>	<u>Title</u>	<u>Page</u>
V-58	Effect of superficial gas velocity on the Sauter mean bubble diameter for FT-300 wax at 265°C in the 0.229 m ID column with the 19 X 1.85 mm perforated plate distributor, and comparison with literature (by photography)	163
V-59	Effect of superficial gas velocity on the Sauter mean bubble diameter for FT-300 wax at 265°C in the 0.241 m ID stainless steel column with the 19 X 1.85 mm perforated plate distributor (photos taken near the center of the column)	165
V-60	Effect of superficial gas velocity on the bubble size distribution for FT-300 wax at 265°C in the 0.241 m ID stainless steel column with the 19 X 1.85 mm perforated plate distributor (by photography)	167
V-61	Effect of distributor type on the bubble size distribution for FT-300 wax at 265°C in the 0.051 m ID column (by photography)	168
V-62	Effect of radial position and superficial gas velocity on the Sauter mean bubble diameter for FT-300 wax at 265°C in the 0.229-0.241 m ID columns with the 19 X 1.85 mm perforated plate distributor (by photography)	170
V-63	Effect of radial position on the bubble size distribution for FT-300 wax at 265°C in the 0.229-0.241 m ID columns with the 19 X 1.85 mm perforated plate distributor (by photography)	172
V-64	Change in normalized liquid level with time during DGD for a dispersion with N bubble size classes	181
V-65	Correlation of bubble rise velocity as a function of bubble diameter for FT-300 wax at 265°C	185
V-66	Effect of temperature and superficial gas velocity on the Sauter mean bubble diameter (a) and gas hold-up (b) for FT-300 wax in the 0.051 m ID column using the 1.85 mm orifice plate distributor (by DGD)	189
V-67	Effect of temperature and superficial gas velocity on bubble size (a) and volume fraction of large bubbles (b) for FT-300 wax in the 0.051 m ID column using the 1.85 mm orifice plate distributor (by DGD)	191

LIST OF FIGURES (contd.)

<u>Figure</u>	<u>Title</u>	<u>Page</u>
V-68	Effect of temperature and superficial gas velocity on the Sauter mean bubble diameter (a) and gas hold-up (b) for Sasol's Arge reactor wax in the 0.051 m ID column using the 1.85 mm orifice plate distributor (by DGD)	192
V-69	Effect of distributor type and superficial gas velocity on the Sauter mean bubble diameter for FT-300 wax at 265°C in the 0.051 m ID column (by DGD)	194
V-70	Effect of distributor type and superficial gas velocity on bubble size (a) and volume fraction of large bubbles (b) for FT-300 wax at 265°C in the 0.051 m ID column (by DGD)	196
V-71	Effect of distributor type and superficial gas velocity on the Sauter mean bubble diameter (a) and gas hold-up (b) for Mobil's reactor wax at 265°C in the 0.051 m ID column (by DGD)	198
V-72	Effect of column diameter and superficial gas velocity on the Sauter mean bubble diameter (a) and gas hold-up (b) for FT-300 wax at 265°C (by DGD)	200
V-73	Effect of column diameter and superficial gas velocity on bubble size (a) and volume fraction of large bubble (b) for FT-300 wax at 265°C (by DGD)	201
V-74	Effect of liquid medium and superficial gas velocity on the Sauter mean bubble diameter (a) and volume fraction of large bubbles (b) at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor (by DGD)	204
V-75	Effect of liquid medium and superficial gas velocity on gas hold-up at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor	206
V-76	Comparison of techniques used to determine the Sauter mean bubble diameter for FT-300 wax at 265°C in the 0.229-0.241 m ID column with the 19 X 1.85 mm perforated plate distributor	214
V-77	Comparison of small bubble diameters estimated from DGD and photographic techniques for FT-300 wax at 265°C in the 0.229 m ID column with the 19 X 1.85 mm perforated plate distributor	217
VI-1	Comparison between experimental gas hold-ups and predictions from the Bach and Pilhofer correlation	228

LIST OF FIGURES (contd.)

<u>Figure</u>	<u>Title</u>	<u>Page</u>
VI-2	Comparison between experimental and predicted gas hold-ups with orifice and perforated plate distributors for flow in the "foamy" regime	235
VI-3	Comparison between experimental and predicted gas hold-ups with orifice and perforated plate distributors for flow in the "slug flow" or "churn-turbulent" regime	237
VI-4	Comparison between experimental and predicted gas hold-ups with the 40 μm SMP distributor for flow in the "foamy" regime	238
VI-5	Comparison between experimental and predicted gas hold-ups with the 40 μm SMP distributor for flow in the "slug flow" regime	239
VI-6	Comparison between experimental specific gas-liquid interfacial areas and predictions for FT-300 wax at 265°C	248
VI-7	Comparison between experimental specific gas-liquid interfacial areas and predictions for Sasol's Arge reactor wax at 265°C	250
VI-8	Comparison between experimental specific gas-liquid interfacial areas and predictions for Mobil's reactor wax at 265°C	251
B-1	Schematic diagram of the top of the dispersion with respect to pressure tap locations	275
C-1	Change in the normalized liquid level as a function of time and superficial gas velocity for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor (by DGD; Run 13-3)	284
C-2	Effect of superficial gas velocity on bubble sizes for FT-300 wax at 200°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor (by DGD)	286
C-3	Effect of superficial gas velocity on bubble sizes for FT-300 wax at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor (by DGD)	287
E-1	Effect of superficial gas velocity, distributor type and temperature on gas hold-up for Mobil's reactor wax in the 0.051 m ID column (composite from Mobil's runs CT-256-4 and -7)	303

LIST OF FIGURES (contd.)

<u>Figure</u>	<u>Title</u>	<u>Page</u>
E-2	Effect of superficial gas velocity, distributor type and temperature on gas hold-up for Mobil's reactor wax in the 0.051 m ID column (composite from Mobil's runs CT-256-5 and -8)	304
E-3	Comparison of hold-ups obtained in studies with different Mobil wax composites at 265°C in the 0.051 m ID column with the 1.85 mm orifice plate distributor	306
E-4	Comparison of hold-ups obtained in the present study with literature values for Mobil waxes with the 1 mm orifice plate distributor	307
E-5	Effect of small quantities of FT-200 on gas hold-up for Mobil's reactor wax in the 0.051 m ID column (composite from Mobil's runs CT-256-4 and -7)	310
E-6	Effect of small quantities of FT-200 on gas hold-up for Mobil's reactor wax in the 0.051 m ID column (composite from Mobil's runs CT-256-5 and -8)	311
E-7	Effect of contamination on gas hold-up for distilled water	312