

FINAL

ALTERNATIVE FUEL AND CHEMICALS FROM SYNTHESIS GAS

Prepared for

AIR PRODUCTS AND CHEMICALS, INC.

Subcontract No. PT5781-B

**TASK 1.3
FISCHER-TROPSCH SUPPORT**

**TOPICAL REPORT
FISCHER-TROPSCH WAX/CATALYST SEPARATION STUDY**

Bechtel Corporation

May 1996



DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

**Portions of this document may be illegible
in electronic image products. Images are
produced from the best available original
document.**

Contents

Section		Page
1	Introduction and Objectives.....	1-1
	1.1 Introduction	1-1
	1.2 Objectives	1-1
2	Separation Process Selection	2-1
	2.1 Design Basis.....	2-1
	2.1.1 Baseline Design	2-1
	2.1.2 Background Information.....	2-1
	2.1.3 Physical Properties.....	2-7
	2.1.4 Design Basis	2-10
	2.2 Separation Techniques.....	2-12
	2.2.1 Potential Techniques.....	2-12
	2.2.2 Detailed Considerations	2-14
	2.3 Initial Screening of Candidate Separation Processes.....	2-15
3	Evaluation of Candidate Processes	3-1
	3.1 Density – Exploiting Wax/Catalyst Density Difference with Sedimentation	3-1
	3.1.1 Operating Principles.....	3-1
	3.1.2 Sedimentation.....	3-3
	3.1.3 Centrifugal Force Devices.....	3-3
	3.1.4 Chemical Enhancement	3-5
	3.2 Filtration – Exploiting Particle Size.....	3-7
	3.2.1 Deep-Bed Filtration	3-7
	3.2.2 Filtration with Screens	3-9
	3.2.3 Membrane Processes.....	3-9

Contents (Cont'd)

Section		Page
3.3	Enhanced Sedimentation – Exploiting Viscosity-Reducing Additives – Exploiting Coagulants	3-14
3.4	High Gradient Magnetic Separation (HGMS) – Exploiting Magnetic Susceptibility.....	3-15
3.5	Modified Kerr-McGee Process	3-15
3.6	Comparison of Separation Processes	3-17
4	Summary and Recommendations	4-1
4.1	Summary.....	4-1
4.2	Recommendations	4-1
5	References	5-1

Appendix

1	The Kerr-McGee ROSE Critical Solvent Extraction Process for F-T Wax/Catalyst Separation	A1-1
2	SASOL's 25 January 1994 Application for a U.S. Patent for a Fischer-Tropsch Synthesis Reactor, Including Internal Filter.....	A2-1
3	Bechtel Interoffice Memorandum	A3-1
4	Bechtel Interoffice Memorandum	A4-1
5	System for Separation of Finely Divided Iron Oxide Catalyst from Liquid Wax in Fischer-Tropsch Synthesis of Transportation Fuels	A5-1

Contents (Cont'd)

Illustrations

Figure		Page
2-1	Baseline Design – Wax/Catalyst Separation with Solvent Extraction	2-2
2-2	Iron Oxide Catalyst Particle Size Measurements by Various Organizations	2-9
2-3	Wax/Catalyst Recovery System.....	2-11
3-1	Typical Sedimentation Equipment	3-4
3-2	Centrifuge Separation	3-6
3-3	General Regions of Liquid-Solid Separation by Filtration	3-8
3-4	Filtration Classification.....	3-10
3-5	Asymmetric and Isotropic Filter	3-13
3-6	Aquafine Magnetic Filter.....	3-16

Tables

Table		Page
2-1	Comparison of Separation Methods	2-15
3-1	Fall Times for Particles of Various Diameters in Sedimentation and Centrifuging Processes.....	3-2
3-2	Comparison of Separation Processes	3-17