

ACKNOWLEDGMENTS

I would like to express my sincere appreciation to my committee chairman, Dr. D. B. Bukur for his patient instruction and continued interest in this research. I thank Dr. M. T. Holtzapple and Dr. G. B. Tatterson for participating on my graduate committee, and to Dr. R. Darby and Dr. H. Graig for allowing me to use their equipment.

I am indebted to the faculty and graduate students of the Chemical Engineering Department at Texas A&M for their cooperation. Dr. S. Patel, Dr. M. Patel, James Daly, W. Zimmerman, and R. Brown provided valuable assistance for which I am very thankful.

Finally, I want to thank the DOE for financing this research project, the Swiss Development Cooperation and the University of Dar-es-Salaam for the fellowship support they provided during my graduate studies.

TO
MY PARENTS

TABLE OF CONTENTS

CHAPTER	Page
I INTRODUCTION	1
II LITERATURE REVIEW	3
A. Gas Flow in Bubble Columns	3
B. Fischer-Tropsch Derived Waxes	3
1. Effect of Temperature	5
2. Effect of Solids	7
3. Effect of Pressure and Gas Type	7
4. Effect of Superficial Gas Velocity on Flow Regimes	8
5. Effect of Column Diameter	9
6. Effect of Liquid Medium	10
7. Effect of Static Liquid Height	10
8. Effect of Distributor Type	11
C. Non-Wax Liquid Mediums	12
D. Thesis Objectives and Motivation	16
III EXPERIMENT	18
A. Experimental Apparatus	18
1. Apparatus Description	18
2. Operation	21
B. Measurements of Average Gas Hold-up	21
1. Hot-Flow Runs	22
2. Cold-Flow Runs	23
C. Measurements of Physical Properties	23
1. Fischer Tropsch Derived Waxes	23
2. Aqueous Mixtures	33
D. Effects of Butanol and CMC on Physical Properties	37
IV AVERAGE GAS HOLD-UP	42
A. Fischer-Tropsch Derived Waxes	42
1. Reproducibility and Effect of Operating Procedure	42
2. Effect of Temperature	45
3. Effect of Column Diameter	51
4. Effect of Distributor Type	53

TABLE OF CONTENTS (Continued)

CHAPTER		Page
IV	AVERAGE GAS HOLD-UP (Cont'd.)	
	B. Pure Liquids	56
	1. Effect of Start-up Procedure	58
	2. Effect of Column Diameter	58
	3. Effect of Distributor Type	61
	4. Effect of Liquid Medium	61
	C. Aqueous Solutions of n-Butanol	65
	1. Effect of n-Butanol Concentration	65
	2. Effect of Start-up Procedure	67
	3. Effect of Column Diameter	67
	4. Effect of Distributor Type	70
	5. Comparison With Other Foaming Mediums	75
	D. Aqueous Solutions of n-Butanol With CMC	75
	1. Effect of CMC Concentration	75
	2. Effect of Column Diameter	80
	3. Effect of Distributor Type	83
	4. Effect of Viscosity on Gas Hold-up	85
V	BUBBLE DYNAMICS	90
	A. Data Acquisition	90
	B. Procedure for Obtaining Bubble Sizes	92
	1. Fischer Tropsch Derived Waxes	93
	2. Pure Liquids	94
	3. Aqueous Solutions of Butanol With CMC	94
VI	SAUTER MEAN BUBBLE DIAMETER	101
	A. FT Derived Waxes	101
	1. Effect of Operating Temperature	101
	2. Effect of Distributor Type	103
	3. Effect of Wax Type	103
	B. Pure Liquids	106
	1. Effect of Distributor Type	106
	C. Aqueous Solutions of n-Butanol	106
	1. Effect of Distributor Type	106
	D. Aqueous Solutions of n-Butanol With CMC	110
	1. Effect of Distributor Type	110
	2. Effect of Column Diameter	112
	3. Effect of Physical Properties	114

TABLE OF CONTENTS (Continued)

CHAPTER	Page
VII CORRELATIONS	116
A. FT Derived Waxes	116
1. Average Gas Hold-up	116
2. Specific Gas-Liquid Interfacial Area	118
B. Pure Liquids	121
1. Average Gas Hold-up	121
2. Specific Gas-Liquid Interfacial Area	125
C. Aqueous Solutions of n-Butanol	129
1. Average Gas Hold-up	129
2. Specific Gas-Liquid Interfacial Area	132
D. Aqueous Solutions of n-Butanol With CMC	134
1. Average Gas Hold-up	134
VIII CONCLUSIONS AND RECOMMENDATIONS	141
NOTATIONS	144
LITERATURE CITED	146
APPENDICES	
A. SUMMARY OF RUNS WITH FT DERIVED WAXES	150
B. SUMMARY OF DGD RESULTS FOR RUNS WITH FT DERIVED WAXES	173
C. SUMMARY OF RUNS WITH NON-WAX LIQUID MEDIUMS	178
D. SUMMARY OF DGD RESULTS FOR RUNS WITH NON-WAX LIQUID MEDIUMS	193

TABLE OF CONTENTS (Continued)

CHAPTER	Page
APPENDICES Cont'd.	
E. PROCEDURES FOR MEASURING PHYSICAL PROPERTIES OF NON-WAX LIQUID MEDIUMS . . .	206
F. DYNAMIC GAS DISENGAGEMENT TECHNIQUE . . .	213
VITA	227

LIST OF TABLES

TABLE	Page
1. Summary of Bubble Column Hydrodynamic Studies Using Waxes	6
2. Summary of Bubble Column Hydrodynamic Studies Using Non-Wax Mediums	13
3. Details of Operating Variables for Runs With FT-Derived Waxes	24
4. Details of Operating Variables for Runs With Pure Liquids	27
5. Details of Operating Variables for Runs With Non-Wax Liquid Mediums	28
6. Physical Properties of Waxes	29
7. Physical Properties of Newtonian Liquid Mixtures at 24 °C	34
8. Physical Properties of Fresh non-Newtonian Liquid Mixtures at 24 °C	35
9. Physical Properties of Spent non-Newtonian Liquid Mixtures at 24 °C	36

LIST OF FIGURES

FIGURE	Page
1. Bubble column flow regime map (from Deckwer <i>et al.</i> 1980).	4
2. Flow diagram of experimental apparatus.	19
3. Sketch of 19x1.85 mm perforated plate distributor.	20
4. Effect of butanol concentration on surface tension and viscosity	38
5. Apparent viscosity versus shear rate for non-Newtonian mixtures	41
6. Effect of operating mode and superficial gas velocity on gas hold-up	43
7. Effect of operating mode and superficial gas velocity on gas hold-up	44
8. Effect of operating temperature and superficial gas velocity on gas hold-up	46
9. Effect of operating temperature and superficial gas velocity on gas hold-up	48
10. Effect of operating temperature and superficial gas velocity on gas hold-up and comparison with literature	49
11. Effect of column diameter and superficial gas velocity on gas hold-up	52
12. Effect of distributor type and superficial gas velocity on gas hold-up	54
13. Effect of distributor type on gas hold-up	55
14. Effect of distributor type and superficial gas velocity on gas hold-up	57
15. Effect of start-up procedure and superficial gas velocity on gas hold-up	59
16. Effect of column diameter and superficial gas velocity on gas hold-up	60

LIST OF FIGURES (Continued)

FIGURE	Page
17. Effect of distributor type and superficial gas velocity on gas hold-up for pure liquids	62
18. Comparison of average gas hold-up for non-foamy mediums	64
19. Effect of butanol concentration and superficial gas velocity on gas hold-up	66
20. Effect of start-up procedure and superficial gas velocity on gas hold-up	68
21. Effect of column diameter and superficial gas velocity on gas hold-up	69
22. Effect of distributor type and superficial gas velocity on gas hold-up	71
23. Effect of distributor type and superficial gas velocity on gas hold-up	72
24. Effect of distributor type and superficial gas velocity on gas hold-up	74
25. Comparison of gas hold-ups for foaming liquids	76
26. Effect of CMC concentration and superficial gas velocity on gas hold-up	77
27. Effect of CMC concentration and superficial gas velocity on gas hold-up	78
28. Effect of CMC concentration and superficial gas velocity on gas hold-up	79
29. Effect of column diameter and superficial gas velocity on gas hold-up	81
30. Effect of column diameter and superficial gas velocity on gas hold-up	82

LIST OF FIGURES (Continued)

FIGURE	Page
31. Effect of distributor type and superficial gas velocity on gas hold-up	84
32. Effect of distributor type and superficial gas velocity on gas hold-up	86
33. Effect of liquid viscosity and superficial gas velocity on gas hold-up	87
34. Effect of liquid viscosity and superficial gas velocity on gas hold-up	88
35. Change in normalized height as a function of time and velocity, example from run B-6	91
36. Bubble rise velocity versus equivalent bubble diameter for FT-300 wax	95
37. Bubble rise velocity versus equivalent bubble diameter for n-butanol.	96
38. Bubble rise velocity versus equivalent bubble diameter for aqueous solutions	99
39. Effect of temperature and superficial gas velocity on Sauter mean bubble diameter	102
40. Effect of distributor type and superficial gas velocity on Sauter mean bubble diameter	104
41. Effect of wax type and superficial gas velocity on Sauter mean bubble diameter	105
42. Effect of distributor type and superficial gas velocity on Sauter mean bubble diameter	107
43. Effect of distributor type and superficial gas velocity on Sauter mean bubble diameter	108
44. Effect of distributor type and superficial gas velocity on Sauter mean bubble diameter	109

LIST OF FIGURES (Continued)

FIGURE	Page
45. Effect of distributor type and superficial gas velocity on Sauter mean bubble diameter	111
46. Effect of column diameter and superficial gas velocity on Sauter bubble mean diameter	114
47. Effect of butanol and CMC concentration on Sauter mean bubble diameter	115
48. Comparison between experimental hold-ups and predictions from Bach and Pilhofer correlation	117
49. Comparison between experimental specific gas-liquid interfacial area and predictions for Sasol reactor wax.	120
50. Comparison between experimental specific gas-liquid interfacial area and predictions for Mobil reactor wax.	122
51. Comparison between experimental hold-ups and hold-ups predicted from literature correlations	124
52. Comparison between experimental hold-ups and hold-ups predicted from literature correlations	126
53. Comparison between experimental hold-ups and hold-ups predicted using Akita and Yoshida correlation within ± 20 % relative deviation	127
54. Scatter plot for specific gas-liquid interfacial area for n-butanol in the 0.051 m ID column	128
55. Comparison between experimental hold-ups and hold-ups predicted using the correlation by Posarac and Tekic (1987) within ± 20 % relative deviation	130
56. Comparison between experimental hold-ups and hold-ups predicted using the correlations by Posarac and Tekic (1987) and Kelkar (1983) within ± 20 % relative deviation	131
57. Scatter plot for specific gas-liquid interfacial area for n-butanol solutions in the 0.051 m ID column	133

LIST OF FIGURES (Continued)

FIGURE	Page
58. Comparison between experimental hold-ups and predicted hold-ups using literature correlations	135
59. Comparison between experimental hold-ups and predicted hold-ups for mixtures containing water, butanol, and CMC for runs with orifice and perforated plate distributors.	139
60. Scatter plot for average gas hold-ups in the 0.051 m ID column using 40 μ m SMP distributor for aqueous solutions of n-butanol with CMC	140
E.1. Schematic diagram of Fann model 50C viscometer	209
E.2. Calibration curves for viscometer using standard liquids.	211
F.1. Disengagement of bubbles after the gas flow is cutoff	215
F.2. Normalized height as a function of time	217
F.3. Plot of normalized height versus time for dynamic gas disengagement analysis	221