Ur	nited S	tates Patent [19]	[11]	Patent Number:	4,480,143
Chang et al.			[45]	Date of Patent:	Oct. 30, 1984
[54]	HYDROCA	ARBON SYNTHESIS	[56] References Cited		
[75]	Inventore	Clarence D. Chang Princeton		U.S. PATENT DOCU	MENTS
[/-]	inventors.	ors: Clarence D. Chang, Princeton; William H. Lang, Pennington, both of N.J.	2,041,840 5/1936 Lazier et al		
[73]	Assignee:	Mobil Oil Corporation, New York, N.Y.			
[21]	Appl. No.:	229,610	[57]	ABSTRACT	
[22]	Filed:	Jan. 28, 1981	A process for converting or synthesizing hydrocarbons from carbon sulfides such as CS ₂ by catalytic hydrogenation over catalysts such ZSM-5 type zeolites. 4 Claims, No Drawings		
[51]		C07C 1/20; C07C 1/00			
[52] [58]					

HYDROCARBON SYNTHESIS

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention is directed to a novel process for converting carbon sulfides with hydrogen to hydrocarbons, particularly aromatics, over ZSM-5 type zeolites which may also contain a metal component having hydrogenation and/or hydrodesulfurization activity. This process is also directed to a means of providing a new inexpensive route directly from carbon sources to synthetic fuels.

2. Description of the Prior Art

Various means have been tried to produce hydrocar- 15 bons in a facile, efficient and inexpensive manner. For example, CS2 has been reacted with hydrogen to yield H₂S and a variety of organic compounds dependent dium. At higher temperatures, lower hydrocarbons 20 ent to those of ordinary life in the sole pursuch as CH are produced and reaction mesuch as CH4 are produced and at lower temperatures reduction of carbon disulfide produces various organic sulfur compounds such as CH₃SH.

U.S. Pat. No. 4,175,928, for example, relates to a process for converting organic sulfur compounds into 25 H2S; a sulfided catalyst having incorporated therein two metal components such as nickel and molybdenum is used in the process.

U.S. Pat. No. 3,894,107 relates to the discovery that hetero organic compounds of the R-X type may be 30 converted to aromatic hydrocarbons by contacting such compounds with a crystalline aluminosilicate zeolite. R stands for an aliphatic hydrocarbon moiety and X stands for a heteroatom such as sulfur, nitrogen, halo-

U.S. Pat. No. 3,894,103 discloses a process wherein lower aliphatic alcohols, carbonyls, ethers, or analogues thereof are converted to higher hydrocarbons by contacting such with a crystalline aluminosilicate zeolite having a silica to alumina ratio of about 60 to 600 to 40 increase the liquid C5+ yield.

SUMMARY OF THE INVENTION

It has now been discovered that carbon sulfides such as CS2 or COS when reacted with H2 over ZSM-5 type 4 zeolites produce highly useful hydrocarbons, especially aromatics. The zeolite may or may not contain a metal component having hydrogenation and/or hydrodesulfurization activity. Since sulfides such as CS2 are readily produced by the reaction of S with C, CH4 or LPG, the 5 herein embodied process is believed to provide a new, novel method for synfuels production.

DESCRIPTION OF THE PREFERRED **EMBODIMENTS**

The zeolites useful herein as mentioned previously are of the ZSM-5 type and include ZSM-5, ZSM-11, ZSM-12, ZSM-35, ZSM-38, TEA mordenite and other similar materials and also their hydrogen counterparts changed, contain ammonium ions or impregnated to contain a cation complement. Examples of useful metal components include Co, Co/Mo, Zn, Zn/Pd, Ni, NiW, and Ni/Mo. Generally speaking, any metal from Groups II or VIII of the Periodic Table may be useful. 65 U.S. Pat. No. 3,702,886 describes and claims ZSM-5; U.S. Pat. No. 3,709,979 describes ZSM-11; ZSM-12 is described by W. German Offenlegungschrifft No.

2,213,109; U.S. Pat. No. 4,016,245 particularly describes ZSM-35 and ZSM-38 is particularly described in U.S. Pat. No. 4,046,859 all of which are incorporated herein in their entirety.

To illustrate the practice of this invention, two ZSM-5 type catalysts were each used to carry out separate reactions wherein CS2 was converted to hydrocarbons. The reaction conditions and products set forth in the Table below are exemplary only and are not meant to limit the invention. The temperature and pressure can vary within wide limits. Preferred is a range of 400° to 1200° F. and a pressure within the range of 100 to 1000 psig. The feed rates used in the reactive process can vary from 0.5 LHSV (liquid hourly space velocity) to about 50 LHSV for CS2 or COS, and 200 to about 10,000 GHSV (gas hourly space velocity) for H₂.

The specific embodiments and details as mentioned hereinabove and disclosed below are for the sole purchanges and modifications may be made without departing from the scope of the invention.

The feasibility of the novel method embodied herein and the wide range of hydrocarbons obtained, especially aromatics, are demonstrated by the data shown in the Table below:

TABLE

TABLE					
	EXAMPLE 1		EXAMPLE 2		
Reaction Conditions					
CS ₂ , LHSV	1		1		
H ₂ , GHSV	400		400		
T, °F.	900		900		
P, psig	250		250		
Catalyst	*HZSM-5	1	50% HZSM-5/Al ₂ O ₃		
•		₹			
		/	50% Co/SiO ₂ **		
CS ₂ Conversion, %	25.6		40.3		
HC, wt. %					
Ci	52.4		44.7		
C ₂	9.2		6.1		
C ₂	1.9		-		
C ₂ C ₃	3.0		3.7		
C ₃	0.3		0.1		
i C ₄	0.2		0.2		
n C ₄	0.2		0.3		
C ₄	_		_		
C ₅ + nonaro	_		tr		
A ₆	1.4		2.6		
A7	5.9		7.7		
A8	8.2		9.5		
A ₉	4.6		18.1		
A ₁₀	0.3		3.2		
A ₁₁ +	12.4		3.8		

prepared in accordance with U.S. Pat. No. 3,702,886 *obtained commercially

The unexpected and surprising efficiency of this process, particularly with respect to providing aromatics is clearly shown in the Table. For example, the HZSM-5 catalysts of the present invention, see Example 1, are about as effective as a cobalt containing catalyst, see such as HZSM-5, etc. They may also be base ex- 60 Example 2, with respect to aromatics. This is most surprising and quite unexpected in view of the fact that HZSM-5 (Example 1) catalyst had a conversion rate for CS₂ of only 25.6% compared to 40.3% for the cobalt containing catalyst of Example 2. Even more surprising is the finding that ZSM-5 type materials catalyze the following reaction: $CS_2+3H_2\rightarrow [CH_2]+2H_2S$ in the absence of a metal hydrogenation component.

We claim:

1. A process for converting as a reactant carbon sulfides selected from the group consisting of CS₂ and COS to a hydrocarbon or mixture of hydrocarbons ranging from C₁ to C₁₁+ wherein at least 25% thereof are C₅ to C₁₁ comprising contacting said carbon sulfides with a ZSM-5 type aluminosilicate zeolite catalyst having a constraint index of about 1 to 12 and having a silica to alumina ratio of at least 12 at about 400° to 1200° F. and a pressure of about 100 to 1000 psig in the presence

of added hydrogen to produce a highly aromatic product.

2. The process of claim 1 wherein the catalyst is selected from the group consisting of ZSM-5, ZSM-11, ZSM-12, ZSM-35, ZSM-38 and their hydrogen forms.

3. The process of claim 2 wherein said catalyst is further comprised of a Group II or Group VIII metal

from the Periodic Table.

4. The process of claim 3 wherein the metals are 10 selected from the group consisting of Co, Co/Mn, Zn, ZnPd, Ni, NiW and Ni/Mo.

15

20

25

30

35

40

45

50

55

60

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO. :

4,480,143

DATED

October 30, 1984

INVENTOR(S):

CLARENCE D. CHANG AND WILLIAM H. LANG

It is certified that error appears in the above—identified patent and that said Letters Patent are hereby corrected as shown below:

In column 3, line 6, " C_{11} " should be $--C_{11}^+$ --.

Bigned and Bealed this

Twenty-sixth Day of March 1985

[SEAL]

Attest:

DONALD J. QUIGG

Attesting Officer

Acting Commissioner of Patents and Trademarks