



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : C01B 3/44, B01J 8/32	A1	(11) International Publication Number: WO 92/21609 (43) International Publication Date: 10 December 1992 (10.12.92)
(21) International Application Number: PCT/US92/04753 (22) International Filing Date: 5 June 1992 (05.06.92) (30) Priority data: 711,762 7 June 1991 (07.06.91) US (71) Applicant: EXXON RESEARCH AND ENGINEERING COMPANY [US/US]; 180 Park Avenue, P.O. Box 390, Florham Park, NJ 07932-0390 (US). (72) Inventors: LAHN, Gerard, Charles ; 4 Butterworth Drive, Morristown, NJ 07960 (US). KAISER, Frederick, John, Jr. ; 41 Cross Road, Morris Plains, NJ 07950 (US). FIATTO, Rocco, Anthony ; 27 Wexford Way, Basking Ridge, NJ 07920 (US).		(74) Agents: SIMON, Jay, S. et al.; Exxon Research and Engineering Company, P.O. Box 390, Florham Park, NJ 07932-0390 (US). (81) Designated States: AT (European patent), AU, BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), LU (European patent), MC (European patent), NL (European patent), NO, SE (European patent). Published <i>With international search report.</i>
(54) Title: CATALYST/HEAT-TRANSFER MEDIUM FOR SYNGAS GENERATION (57) Abstract Synthesis gas, hydrogen and carbon monoxide, as produced in a fluid-bed or spouted-bed process by reacting methane or a lower alkane with steam and oxygen in the presence of essentially non-catalytic, heat carrying solids with periodic addition of a steam-reforming catalyst for maintaining a level of activity sufficient within 250 °F of the approach to equilibrium.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	MI	Mali
AU	Australia	FR	France	MN	Mongolia
BB	Barbados	GA	Gabon	MR	Mauritania
BE	Belgium	GB	United Kingdom	MW	Malawi
BF	Burkina Faso	GN	Guinea	NL	Netherlands
BG	Bulgaria	GR	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IE	Ireland	RO	Romania
CA	Canada	IT	Italy	RU	Russian Federation
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark	MG	Madagascar		
ES	Spain				

- 1 -

CATALYST/HEAT-TRANSFER MEDIUM FOR SYNGAS GENERATIONFIELD OF THE INVENTION

This invention relates to a fluid-bed or spouted-bed process for preparing synthesis gas, carbon monoxide and hydrogen, from lower alkanes, preferably methane, in the presence of both relatively inert solids acting primarily as heat carriers and small amounts, relative to the heat carrying solids, of a catalytic material.

More particularly this invention relates to a process for reacting a lower alkane, e.g., methane, with oxygen in the presence of other gas phase components, preferably steam at elevated temperatures and pressures, and in the presence of both fluidized, relatively inert solids and catalytic solids.


In fluid-bed processes the entire solids inventory of both catalytic and inert solids is in a state of fluidization, while in spouted-bed processes only that portion of the bed through which the gases are injected are in a fluidized state.

BACKGROUND OF THE INVENTION

The production of synthesis gas by either partial oxidation or steam-reforming is well known and there are extensive literature references to these processes. The processes may be used separately or they may be combined. Thus, the steam-reforming reaction is highly endothermic and is described as:




while the partial oxidation reaction is highly exothermic and is described by:




- 2 -

The combined reaction employing a 2/1 CH₄/O₂ feed ratio is described as:



In addition to these reactions, the mildly exothermic water gas shift reaction also occurs:



The representation of the combined process shows that the ratio of produced hydrogen to carbon monoxide is 2/1; the approximate stoichiometric hydrogen/carbon monoxide ratio for producing higher hydrocarbons by a hydrocarbon synthesis process, such as the Fischer-Tropsch process over a catalyst with little or no water gas shift activity.

A number of patents illustrate these processes, and U.S. Patent No. 4,888,131 contains an extensive, but not exhaustive listing thereof.

Fluid bed processes are well known for the advantages they provide in heat and mass transfer characteristics. Such processes allow for substantially isothermal reactor conditions, and are usually effective in eliminating temperature runaways or hot spots; however, with O₂ injection while complete elimination of hot spots is impossible although the fluid bed does tend to minimize the intensity thereof. They are not, however, without their disadvantages: catalyst strength or attrition resistance is important for maintaining the integrity of the catalyst and minimizing the formation of fine particles that may be lost from the system, especially those particles not recoverable by use of cyclones and deposited in down stream equipment causing fouling or reverse reactions as temperature is decreased; erosivity, or the tendency to erode equipment must be contained, since attrition resistance is often an inverse function of erosivity.

- 3 -

Additionally, the relatively high temperatures, e.g., above about 1650°F, found in reforming reactions where oxygen is present can cause agglomeration of the catalyst particles leading to lower catalytic efficiency (e.g., lower conversion), larger particles that are more difficult to fluidize, greater wear on equipment due to greater momentum and impact forces, and clogging of lines. For example, a common catalytic material, nickel, even when deposited in small amounts on a suitable carrier, e.g., less than about 5 wt% nickel on a support, tends to soften at reaction temperatures (due to its reactivity with the support phase with concomitant formation of reactive/lower melting mono- and polymetallic oxide phases), which become sticky, and generally lead to particle agglomeration. Particle agglomeration, in fact, tends to increase as the amount of nickel present in the catalyst bed increases or as the Ni containing phase is subjected to multiple oxidizing and reducing cycles as it is transported through the fluid bed. The behavior of Ni/Al₂O₃ in H₂ and steam rich environments has been reported, E. Ruckenstein et al, J. Catalysis 100 1-16 (1986). Thus, maintaining the amount of nickel at rather low levels in the catalyst bed minimizes particle agglomeration. On the other hand sufficient nickel is required for providing economical feed conversions to synthesis gas, i.e., within about 200°F approach to equilibrium, thereby minimizing the level of CH₄ exiting the syngas generation zone.

Processes similar to fluid-bed steam-reforming processes for the preparation of synthesis gas are also illustrated by US patent 4,758,375 and European patent publication 0163 385 B1 relating to spouted-bed technology and the use of inert materials in the bed.

An object of this invention, therefore, is taking advantage of fluid-bed or spouted-bed processes for the production of synthesis gas from lower alkanes, e.g., C₁-C₄, feeds while substantially eliminating particle growth at elevated temperatures. Another object of this invention is approaching a minimum nickel concentration in the reactor while continuing to provide economic conversion levels.

- 4 -

SUMMARY OF THE INVENTION

These objects and other objects of this invention are met by conducting a fluid-bed or spouted-bed, steam-reforming, partial-oxidation process involving a lower alkane feed, e.g., methane, at elevated temperatures in the presence of non-catalytic or essentially non-catalytic, heat carrying solids, and periodically injecting sufficient catalytic material to maintain conversion levels of less than or equal to a 250°F approach to equilibrium. The invention thus minimizes the total amount of catalytic material in the fluid-bed reaction zone at any point in time, thereby minimizing any agglomeration or sintering effects due to the presence of catalytic material, and allows for conducting the reaction at higher temperatures approaching the heat limit of the non-catalytic solids. Higher operating temperatures, in turn, provide better conversion of feed to synthesis gas.

DETAILED DESCRIPTION OF THE INVENTION

The steam-reforming, partial-oxidation process contemplated herein operates in a reactor wherein at least one part of the solids inventory is in a fluidized state and wherein heat carrying or heat transfer materials are suspended in a flowing fluid at average bed temperatures above about 1650°F, preferably at or above about 1700°F. Reaction pressures may vary widely, for example, from about atmospheric pressure to about 100 atmospheres. Where the product synthesis gas will be used in hydrocarbon synthesis reactions, the pressure may be chosen so that intermediate recompression of the synthesis gas can be avoided and the synthesis gas will flow directly, after some product separation and fines recovery, to the hydrocarbon synthesis reactor, e.g., at pressures of about 10-50 atmospheres, preferably 10-40 atmospheres, more preferably 20-40 atmospheres. By virtue of this invention the high end of the temperature range is no longer limited by catalyst disintegration or catalyst agglomeration and the temperature may range to within about 50°F of the softening point of the heat carrying, essentially non-catalytic materials. (By non-catalytic we mean that the steam-reforming or partial oxidation

- 5 -

process is either not catalyzed or only poorly catalyzed by the heat carrying materials. Thus, the heat carrying solids are inert or substantially inert for this steam-reforming or partial-oxidation reaction.) More preferably, however, average bed temperatures may range from about 1650°F to 2000°F, still more preferably from about 1700°F to about 1800°F at the preferred operating pressure of 20-40 atm. As the preferred pressure decreases to about 10-20 atm, the preferred operating temperature will be decreased accordingly to maintain desired methane conversion.

The feed material to be reformed is any reformable alkane, usually a lower alkane, e.g., C₁-C₄, preferably comprising methane or natural gas which contains a high concentration of methane, e.g., greater than about 70% methane, preferably greater than 80% methane, more preferably, greater than 90% methane based on the total carbon content of the feed. Such feed gases will likely contain up to about 10% ethane, up to about 3% propane and trace amounts of C₄-C₈. Condensate and known contaminants, such as hydrogen sulfide, in the gas should be removed, e.g., by well known processes. Typical feeds may also contain some CO₂ and nitrogen as well as some CO, H₂, olefins and oxygenated products from recycle operations, e.g., from Fischer-Tropsch processes.

The heat carrying solids may be any fluidizable material that maintains its integrity at reaction conditions. These materials may be Group II metal oxides, rare earth oxides, alpha alumina, modified alpha aluminas, or alpha alumina containing oxides.

The heat carrying materials are generally attrition resistant at reaction conditions and have a mean particle diameter ranging from about 20 to 150 microns, preferably 30-150 microns, more preferably 30-120 microns. Alumina materials, especially fused tabular alumina, described in US Patent Nos. 4,888,131 and 4,952,389 are particularly applicable for heat carrying materials and the description of the alumina materials therein is hereby incorporated herein by reference. Generally, these materials are at least about 98% alpha alumina with substantially no silica. Silica tends to volatilize to Si(OH)₄ at

- 6 -

reaction temperatures, impairing the integrity of the particle. Silica content is, therefore, less than about 1 wt%, preferably less than about 0.5 wt%. Preferred materials are alpha aluminas, tabular or fused, and rare earth stabilized alpha aluminas, e.g., containing about 0.1 to 1.0 wt% rare earth.

Materials useful as heat carrying solids generally have rather low surface areas, e.g., less than about 2 m²/gm, usually less than about 1 m²/gm.

The heat carrying materials are substantially inert or non-catalytic with respect to the steam-reforming reaction. Consequently, even though not preferred, some of these materials may be comprised of spent or deactivated catalyst. The reaction itself may lead to deactivation of the catalyst, particularly nickel containing catalysts, which may then be used as heat carrying solids. The deactivation rate of an individual catalyst will be a function of its chemical and physical properties as well as the synthesis gas generation operating conditions. As a given catalyst is being used, it will be possible to determine the precise deactivation rate, and from that the rate at which fresh catalyst will need to be added.

The catalyst used herein may be any conventional steam-reforming catalyst, or autothermal or combined reforming catalyst. Such catalysts can be described as being selected from the group consisting of uranium, Group VII metals, and Group VIII noble and non-noble metals. The metals are generally supported on inorganic refractory oxides similar to the heat carrying materials already described. Preferred catalyst metals are the Group VIII metals, particularly nickel. In the case of nickel, any nickel containing material is useful, e.g., nickel supported on alpha alumina, nickel aluminate materials, nickel oxide, and preferably a supported nickel containing material.

The catalyst may have a similar particle size distribution as that found in the heat carrying material or it may have a somewhat larger particle size, e.g., from 70-250 microns or larger. The larger

- 7 -

particles may be more sintering resistant. Even though more sintering prone, more finely divided catalyst, $< 70\mu$, may be desired because their fluid dynamic properties make them more accessible to the gas phase reactants.

The amount of catalyst in the bed is that sufficient to bring the activity to within 250°F of equilibrium, preferably to within 100°F of equilibrium, more preferably to within 50°F of equilibrium when the overall reaction is being carried out at relatively high pressures, e.g., 20-40 atm where achieving high levels of CH_4 conversion would otherwise be difficult.

The steam-reforming reaction is equilibrium limited. That is, at any particular reaction temperature an equilibrium conversion can be calculated based on the partial pressure of the gaseous components of the system and the relative rate constants of the forward and reverse reactions. This calculation is easily established and carried out by one skilled in the art. However, calculating the equilibrium conversion at any particular temperature is not a part of this invention. The only importance it plays is that the activity of the catalyst is such that the conversion of feed, e.g., methane, to synthesis gas is such that it is equal or greater to that which would be obtained within 250°F approach to the equilibrium conversion for a particular temperature. Thus the approach to equilibrium is simply another way of measuring effective activity of the catalyst-heat transfer solids mixture.

In order to minimize the ability of a catalyst, e.g., nickel containing catalyst, to cause particle agglomeration, the amount of nickel containing particles in the reaction bed should be minimized while maintaining sufficient nickel for providing adequate catalyst activity. Consequently, the nickel loading on a supported particle should be reasonably high, for example, 1 to 20 wt%, bearing in mind that the support usually has a low surface area, with little porosity and can hold relatively low amounts of catalytic metal. The nickel loading in the bed which is constituted of heat carrying, relatively inert particles and supported nickel, catalytic particles should be at

- 8 -

least about 0.01 wt% based on total bed solids, preferably at least about 0.02 wt%, more preferably about 0.02 wt% to about 3.0 wt%, and most preferably about 0.2 to 1.5 wt%. This loading is for nickel acting as a catalyst for the steam reforming reaction, i.e., active nickel, since there may be some totally or substantially deactivated nickel, i.e., spent nickel, in the reaction zone acting as a heat carrying solid. Since the nickel loading on the catalytic particle may vary widely, as stated above, the amount of nickel containing catalytic solids can be easily calculated based on the total bed weight the weight of nickel in the total bed, and the nickel loading on the nickel containing solids.

The catalyst containing material may be added continuously to the fluid-bed or may be added at regular intervals. Significant increases or decreases in the weight of the fluidized material should be avoided so as not to disturb the fluidizing characteristics of the bed. Thus, the rate and timing of the addition of catalyst should be, generally, balanced by the normal losses from any fluid-bed system, that is, fines or materials of less than about 20 microns mean diameter which cannot be trapped by cyclones for return to the bed, and other materials, such as spent catalyst that is removed from time to time from the fluid-bed.

Regardless of whether active catalytic material is continuously fed to the fluid-bed or spouted-bed or injected at regular or irregular intervals, the rate and timing of catalyst addition is such that conversion of feed, e.g., methane, and feed leak or methane leak, i.e., the volume % of unconverted feed or methane in the product gases, is within 250°F of equilibrium. One skilled in the art can easily picture a plot of activity (ordinate) v. time (abscissa) where the activity line is relatively horizontal (constant addition of fresh or active catalyst) or effects a saw tooth-type curve (periodic addition of fresh or active catalyst where activity decreases with time and then jumps with each injection of catalyst).

The unconverted feed or methane leaving the fluid-bed as product gas is usually less than about 10%, preferably less than about

- 9 -

- 8%, more preferably less than about 5% based on the total level of the hydrocarbon or methane being fed to the reactor.

The fluidized reaction zone may contain a fluid bed of particles or a spouted bed of particles. The design and engineering of fluid-bed or spouted-bed reactors for the conversion of methane or lower alkanes to synthesis gas is easily accomplished with relationships and techniques well known in the art, see, e.g., O. Levenspiel and K. Dunii, Fluidization Engineering, Wiley, New York (1969) and references therein and see K. Mathane and N. Epsteain, Spouted Beds, Academic Press, New York, 1974 and references therein. Fluid bed processes are preferred.

The steam-reforming partial-oxidation reaction is carried out in the presence steam and oxygen. The alkane feed to steam molar ratio is at least about 1 preferably about 1 to 3, more preferably 1.5 to 2.5. The oxygen to alkane feed molar ratio is about 0.2 to 1.0, preferably 0.4 to 0.6. The O₂ is added to provide the sensible heat for reactants and to maintain the overall reaction temperature at a desired level. When oxygen is employed, the alkane feed and oxygen should be separately diluted with steam and/or CO₂ and preheated before injection into the fluidized bed reaction zone. The ratio of steam to CO₂ is chosen so as to achieve the desired H₂/CO product ratio.

Example

A refractory lined three foot diameter fluid-bed reactor was charged with about 14 klb of 55-65 micron average diameter fused alumina and 50 lb. of an 8 wt% Ni catalyst supported on 0.3 wt% La-Al₂O₃ support, 40-100 micron average diameter. The bed of heat carrying solids and Ni catalyst contained ca. 0.025-0.03 wt% nickel. The system was initially brought to temperature via in situ combustion of methane until the desired operating temperature was approached.

Natural gas plus steam and carbon dioxide were introduced at the bottom of the reactor through an 8 inch o.d. center post with four

- 10 -

1.04 inch i.d. tubes angled 30 degrees downward from horizontal. These tubes were symmetrically disposed around the outer circumference of the post. This feed was simultaneously introduced through four similar tubes positioned symmetrically around the vessel wall.

Oxygen together with nitrogen, carbon dioxide, other inert diluent gases or mixtures thereof were introduced through eight nozzles evenly spaced around the reactor wall at a level about 3 feet above the methane feed zone. Each nozzle terminates in three 0.277 inch i.d. tubes; the center tube is aimed at the vertical center line of the reactor at an angle 30 degrees below horizontal. The outer tubes are angled 30 degrees to either side of the center tube and are on a horizontal axis.

The system was operated for about ten days after which time an additional 325 lb. batch of the Ni reforming catalyst was added to the bed to give an overall Ni loading level of 0.2-0.3 wt%. Solids that were eluded from the bed were recycled so as to maintain a nearly constant inventory during this operating period.

Total feed rates (moles/hr) to the reactor were: 150 methane, 108 steam, 71 oxygen, 48 carbon dioxide and less than 10 of nitrogen. The system was operated at an average bed temperature of 1700°F at a pressure of 360 psia over a 15 day period during which nearly stable activity, i.e., little deactivation, was observed and total solids attrition as measured by the formation of particles with less than 38 microns average diameter and agglomeration as measured by the formation of particles with over 90 microns average diameter were minimal.

On-line analysis showed 80-95% overall conversion with the outlet stream containing hydrogen and carbon monoxide with an H_2/CO molar ratio of ca. 1.9-2.0, steam, carbon dioxide and nitrogen. This stream was shown to have less than 5% volume of methane present at the end of the 15 day operating period.

- 11 -

This example demonstrates the utility of a fluid-bed comprised of non-catalytic heat carrying solids with low levels of a nickel containing steam reforming catalyst to produce synthesis gas from methane with high overall efficiency.

In the example, the amount of nickel added to the bed was more than sufficient to maintain the conversion to well within a $\sim 100^{\circ}\text{F}$ approach to equilibrium. Consequently, the rate of deactivation, e.g., the activity half life, is rather relatively long for this amount of nickel. However, with increasing time of operation the activity will continue to fall, and another injection of nickel containing solids will be required to maintain a desired conversion and overall approach to equilibrium.

If the amount of nickel added to the system was less than shown in the example, the rate of deactivation would increase faster with time and another nickel addition would become necessary in a shorter time period. Thus, the periodicity of nickel addition is a function of the amount of nickel added to the bed, and the deactivation rate with additional nickel being required to maintain the desired activity and overall approach to equilibrium.

- 12 -

CLAIMS:

1. A process for converting a feed comprising methane to a product comprising hydrogen and carbon monoxide which comprises:

(a) reacting the feed in a fluidized reaction zone at elevated temperatures with oxygen in the presence of a first, essentially non-catalytic heat carrying solids;

(b) periodically adding to the reaction zone a second solid comprising a nickel containing steam reforming catalyst; and

(c) maintaining a methane leak in the product equivalent to no more than a 250°F approach to equilibrium.

2. The process of claim 1 wherein steam is present in the reaction zone.

3. The process of claim 1 wherein CO₂ is present in the reaction zone.

4. The process of claim 1 wherein the steam reforming catalyst comprises about 1-20 wt% nickel on a carrier.

5. The process of claim 4 wherein the heat carrying solid is comprised of alumina.

6. The process of claim 5 wherein the alumina is stabilized with a rare earth element or its oxide.

7. The process of claim 1 wherein the active nickel inventory, based on total solids in the reaction zone, is at least about 0.01 wt%.

8. The process of claim 7 wherein the reaction temperature is at least 1650°F.

- 13 -

9. The process of claim 7 wherein the reaction pressure ranges from about 10-50 atmospheres.

10. A process for converting a feed comprising methane to a product comprising hydrogen and carbon monoxide which comprises:

a) reacting the feed in a fluidized reaction zone at a temperature above about 1650°F in the presence of oxygen, steam, and carbon monoxide, and also in the presence of a first, essentially non-catalytic heat carrying solids;

b) periodically adding to the reaction zone a second solid comprised of a nickel containing steam reforming catalyst and obtaining an active nickel loading in the bed of at least about 0.02 wt%.

c) maintaining a methane leak in the product equivalent to no more than a 250°F approach to equilibrium.

INTERNATIONAL SEARCH REPORT

PCT/US 92/04753

International Application No

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all)⁶

According to International Patent Classification (IPC) or to both National Classification and IPC

Int.Cl. 5 C01B3/44; B01J8/32

II. FIELDS SEARCHEDMinimum Documentation Searched⁷

Classification System

Classification Symbols

Int.Cl. 5

C01B ; B01J

Documentation Searched other than Minimum Documentation
to the Extent that such Documents are Included in the Fields Searched⁸**III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹**

Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
A	GB,A,1 333 738 (UNION CARBIDE CORPORATION) 17 October 1973 see page 1, line 13 - page 2, line 15 see claims 1,9 ---	1,10
A	EP,A,0 335 668 (EXXON RESEARCH AND ENGINEERING COMPANY) 4 October 1989 cited in the application see column 1, line 56 - column 5, line 65 see claims ---	1-5,7-10
A	EP,A,0 164 864 (THE BRITISH PETROLEUM COMPANY PLC) 18 December 1985 cited in the application see page 2, line 14 - page 5, line 7 see claims 1-8,11-14 --- -/-	1-5,7-10

¹⁰ Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search

Date of Mailing of this International Search Report

11 SEPTEMBER 1992

17. 09. 92

International Searching Authority

Signature of Authorized Officer

EUROPEAN PATENT OFFICE

VAN DER POEL W.

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
A	EP,A,0 163 385 (THE BRITISH PETROLEUM COMPANY PLC) 4 December 1985 cited in the application see page 2, line 1 - page 4, line 19 see claims 1,5,6,9,10 ---	1-3,8-10

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO. US 9204753
SA 61036**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 11/09/92

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB-A-1333738	17-10-73	BE-A- 759201	21-05-71
		SE-A- 7406018	06-05-74
		US-A- 3790036	05-02-74

EP-A-0335668	04-10-89	AU-A- 3172089	28-09-89
		US-A- 4888131	19-12-89

EP-A-0164864	18-12-85	AU-B- 575393	28-07-88
		AU-A- 4179285	07-11-85
		DE-A- 3565515	17-11-88
		WO-A- 8505094	21-11-85
		JP-A- 60239301	28-11-85
		US-A- 4758375	19-07-88

EP-A-0163385	04-12-85	AU-B- 575395	28-07-88
		AU-A- 4212685	01-11-85
		CA-A- 1237149	24-05-88
		DE-A- 3565514	17-11-88
		WO-A- 8504647	24-10-85
		JP-T- 61501773	21-08-86
		US-A- 4767569	30-08-88
