



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C01B 3/52, B01D 53/52	A1	(11) International Publication Number: WO 98/55392 (43) International Publication Date: 10 December 1998 (10.12.98)
(21) International Application Number: PCT/US98/11743 (22) International Filing Date: 5 June 1998 (05.06.98) (30) Priority Data: 60/048,784 6 June 1997 (06.06.97) US (71) Applicant: TEXACO DEVELOPMENT CORPORATION [US/US]; 2000 Westchester Avenue, White Plains, NY 10650 (US). (72) Inventors: WALLACE, Paul, S.; 1110 Cheyenne Meadows, Katy, TX 77450 (US). ANDERSON, M., Kay; 2927 Nancy Bell Lane, Missouri City, TX 77459 (US). FAIR, DeLome, D.; 4443 Girl Scout Lane, Friendswood, TX 77546 (US). (74) Agent: KAMMERER, Patricia, A.; Arnold, White & Durkee, P.O. Box 4433, Houston, TX 77210 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: ACID GAS SOLVENT FILTRATION SYSTEM		
(57) Abstract <p>The invention is a process for separating acid gases from synthesis gas and treating the resulting solids. A mixture comprising synthesis gas and acid gas is contacted with a fluid that reacts with said acid gas to form a particulate solid dispersed in a fluid. The slurry comprising fluid and particulate solid is filtered to separate said particulate solid from said fluid by means of a regenerable filter. The particulate solids are removed from the regenerable filter by back-washing with a back-washing fluid to form a pumpable slurry comprising a mixture of particulate solids and back-washing fluid. The slurry is gasified to form synthesis gas and vitrified solids.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

- 1 -

ACID GAS SOLVENT FILTRATION SYSTEM

CROSS REFERENCE TO PATENTS

This application claims priority from provisional patent application serial number 60/048,784 filed on June 6, 1997, entitled ACID GAS SOLVENT FILTRATION SYSTEM.

FIELD OF THE INVENTION

The invention relates to removing acid gases from syngas, and more particularly to separating and recycling the resulting particulate solids to the gasification reactor.

BACKGROUND OF THE INVENTION

The production of syngas from the solid and liquid carbonaceous fuels, especially coal, coke, and liquid hydrocarbon feeds, has been utilized for a considerable period of time and has recently undergone significant improvements due to the increased energy demand. Syngas may be produced by heating carbonaceous fuels with reactive gases, such as air or oxygen, often in the presence of steam in a gasification reactor to obtain the fuel gas which is withdrawn from the gasification reactor. The syngas is then subjected to several cleansing operations to rid it of various contaminants which are formed or liberated from the feed during the gasification operation. These materials can readily become contaminate down stream process units if not properly treated during the gasification operation.

For example, materials often found in the syngas include hydrogen sulfide, ammonia, cyanides, and particulates in the form of carbon and trace metals. The extent of the contaminants in the feed is determined by the type of feed and the particular gasification process utilized as well as the operating conditions. In any event, the removal of these contaminants is critical to make gasification a viable process.

As the product gas is discharged from the gasifier, it is usually subjected to a cooling and cleaning operation involving a scrubbing technique wherein the gas is introduced into a scrubber and contacted with a water spray which cools the gas and removes particulates and ionic constituents from the syngas. The initially cooled gas may then be treated to desulfurize the gas prior to utilization of the product gas.

- 2 -

SUMMARY OF THE INVENTION

The invention is a process for separating acid gases from synthesis gas and treating the resulting solids. A mixture comprising synthesis gas and acid gas is contacted with a fluid that reacts with said acid gas to form a slurry of particulate solid dispersed in a fluid and synthesis
5 gas. The slurry comprising fluid and particulate solid is separated from the synthesis gas in a conventional separator or by other means. The slurry is then filtered to separate said particulate solid from said fluid by means of a regenerable filter. The particulate solids are removed from the regenerable filter by back-washing with a back-washing fluid to form a pumpable slurry comprising a mixture of particulate solids and back-washing fluid.

DETAILED DESCRIPTION OF THE INVENTION

As used herein, a "fluid that reacts with acid gas" includes fluids that preferentially dissolve acid gases as well as fluids that contain one or more compounds that are either dissolved, dispersed, or suspended therein that react with acid gases. The fluid itself may be an inert.

As used herein, "acid gases" comprise hydrogen sulfide, carbon dioxide, or a mixture thereof. Other trace acid gases may be present. The fluid may react with one or both of these acid gases. Typical fluids may include an amine such as ethanolamine. The fluids may be solvents such as lower monohydric alcohols, such as methanol, or polyhydric alcohols such as ethylene glycol and the like.

As used herein, "synthesis gas" or "syngas" comprises gas comprising carbon monoxide, hydrogen, and occasionally inerts such as nitrogen.

As used herein, a "regenerable filter" is a filter that, as it becomes loaded and partially plugged with solids, can be regenerated. regeneration is usually accomplished by removing the filter from service, and then reversing the flow direction and back-washing particles from the
25 filter face. The backwashed material is a slurry that is advantageously isolated from the process stream. Then, when sufficient material has been backwashed, the direction of flow is again reversed and the filter is put back into service.

The invention is a process for separating acid gases from synthesis gas and treating the resulting solids. Syngas may be produced by heating carbonaceous fuels with reactive gases,

- 3 -

such as air or oxygen, often in the presence of steam in a gasification reactor to obtain the fuel gas which is withdrawn from the gasification reactor. The syngas so manufactured often contain contaminants such as acid gases. A mixture comprising synthesis gas and acid gas is contacted with a fluid that reacts with said acid gas to form a particulate solid dispersed in a fluid and
5 synthesis gas. Contacting is usually in a counter-current bubble tray or packed tower, but any type of contacting, including jet scrubbers, reverse jet scrubbers, and venturi scrubbers may be used. The type of contacting apparatus is not important.

Similarly, the type of fluid that reacts with the acid gas is not important. There are many fluids, particulates, and suspensions known to the art to remove acid gases. See, for example,
10 U.S. Patent 4,039,619, U.S. Patent 4,052,176, U.S. Patent 4,496,371, U.S. Patent 4,769,045, U.S. Patent 5,289,676, and U.S. Patent 5,447,702, the disclosures of which are incorporated herein by reference. The fluid may contain an amine such as diethanolamine, methanol, N-methyl-pyrrolidone, or a dimethyl ether of polyethylene glycol. The fluid may contain particulate iron, caustic salts, carbonates, iron oxides, nickel, nickel oxides, or a combination
15 thereof.

The slurry comprising fluid and particulate solid is separated from the synthesis gas in a separation zone in a tower, in a conventional separator, or by other means. Separation of a slurry from a gas is well known in the art.

The slurry is then filtered to separate said particulate solid from said fluid by means of a
20 regenerable filter. It is often advantageous to have pre-concentration steps such as settling in a settler or centrifuging to increase the solids load of the slurry prior to filtering. However, the slurry can be filtered without pre-concentration.

The slurry is filtered by being forced by a pressure drop through filters. The filters remove a fraction, often more than 70%, of the solids in the slurry. The filters allow fluid, and
25 occasionally some solids, to pass through and be recycled to the contactor. As these solids accumulate on the filter, a filter cake is formed. The differential pressure increases until it reaches a point where flow through the filter is impaired. At some point before the filter is completely plugged, the filter is taken out of service.

- 4 -

The fluid that reacts with acid gas is expensive, so it may be advantageous to displace this fluid with a less expensive back-washing fluid. It is preferred to displace the fluid that reacts with acid gas through the filter in the same direction that the process normally flows, so as to not load the fluid that reacts with acid gas with solids. The fluid displacing the fluid that reacts with acid gas is not critical. The fluid that reacts with acid gas can be displaced with among other things water, a hydrocarbon, an alcohol, a gas, or a vapor. It is advantageous to displace the fluid that reacts with acid gas with the back-washing fluid.

The particulate solids are removed from the regenerable filter by back-washing with a back-washing fluid to form a pumpable slurry comprising a mixture of particulate solids and back-washing fluid. This slurry can be treated as waste or can be recycled to the gasification reactor wherein organics will be gasified, and the particulates will be vitrified, thereby rendering both environmentally harmless. The back-washing fluid should be compatible with its subsequent fate. The back-washing fluid can be water, a hydrocarbon, an alcohol, or other compatible fluid. Of course, it may be simplest and most economical to use fluid that reacts with acid gas as the back-washing fluid. The back-washing fluid need not necessarily be miscible with the fluid that reacts with acid gas, though it is often advantageous that it be so. Water is often preferred, since the water is inexpensive and may itself be a waste stream from another process.

The regenerable filter can be any type of back-washable filter. One preferred commercial embodiment is the sock filter. This is a fabric filter covering an interior support into which fluids can enter and be withdrawn. The process stream flows from outside the sock, through the fabric of the sock, and into the interior support. The solids accumulate on the outside of the sock until they are backwashed.

It is advantageous to have two or more socks capable of running in parallel in a system. A control system can place one filter off line by isolating it from the contactor. Then, advantageously, the fluid that reacts with acid gas can be displaced from the filter. Finally, fluid can be injected through the center support and outward through the sock at a velocity sufficient to remove the particulate solids. Then, the back-washing fluid is advantageously displaced by fluid that reacts with acid gas, and the filter is brought back into service.

- 5 -

It is advantageous that the slurry be pumpable. This reduces the handling costs, and allows easy recycling to the gasification reactor. The pumpable slurry is advantageously pumped back into the gasification reactor. The liquid and any organics are gasified in the reactor. The solids are vitrified, which stabilizes the solids for non-hazardous disposal.

- 6 -

CLAIMS:

1. A process for separating acid gases from synthesis gas comprising
 - a. contacting a mixture comprising synthesis gas and acid gas with a fluid that reacts with said acid gas to form a particulate solid dispersed in a fluid and synthesis gas,
5
 - b. separating the synthesis gas from a slurry comprising fluid and particulate solid,
 - c. separating said particulate solid from said fluid by means of a regenerable filter,
 - d. back-washing said particulate solid from said regenerable filter with a back-washing fluid to form a pumpable slurry comprising a mixture of particulate
10 solids and back-washing fluid.
2. The process of claim 1 wherein the fluid that reacts with acid gas comprises an amine.
3. The process of claim 1 wherein the particulate solid comprises iron sulfide.
15
4. The process of claim 1 wherein the back-washing fluid comprises water.
5. The process of claim 1 wherein the fluid that reacts with acid gas comprises an iron compound.
20
6. The process of claim 1 wherein the regenerable filter is a sock filter.
7. The process of claim 1 wherein a plurality of sock filters is employed in step (c).
- 25 8. The process of claim 1 separating said particulate solid from said fluid by means of at least one of at least two regenerable filters, and further comprising the step of controlling the process such that at least one filter is separating said particulate solid from said fluid that reacts with acid gas while at least one regenerable filter is backwashed.

- 7 -

9. The process of claim 1 wherein the fluid that reacts with said acid gases in step (a) is employed as a back-washing fluid in step (d).

10. The process of claim 1 further comprising pumping said pumpable slurry to a gasification
5 reactor, wherein the slurry is gasified to form synthesis gas and vitrified solids.

11. The process of claim 1 wherein the back-washing fluid comprises a compound selected from the group consisting of a hydrocarbon, an alcohol, water, and mixtures thereof.

10 12. The process of claim 1 that further comprises displacing the fluid that reacts with an acid gas from the regenerable filters with a compound selected from one or more of a hydrocarbon, an alcohol, water, or other back-washing fluid prior to back-washing.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/11743

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 C01B3/52 B01D53/52

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C01B B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
A	EP 0 013 049 A (SHELL INT RESEARCH) 9 July 1980 see example 1	1
A	GB 1 102 943 A (ALLIED CHEMICAL CORPORATION) 14 February 1968 see example 1	1
A	US 4 039 619 A (STEINER PETER) 2 August 1977 see claim 1	1
	--- -/--	



Further documents are listed in the continuation of box C



Patent family members are listed in annex

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

17 September 1998

Date of mailing of the international search report

25/09/1998

Name and mailing address of the ISA

European Patent Office, P B 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Clement, J-P

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/11743

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
A	<p> DATABASE WPI Section Ch, Week 7715 Derwent Publications Ltd., London, GB; Class E36, AN 77-26167Y XP002077793 & JP 52 028470 A (HITACHI LTD) , 3 March 1977 see abstract ----- </p>	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/11743

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0013049 A	09-07-1980	AR 229782 A	30-11-1983
		AU 531343 B	18-08-1983
		AU 5406279 A	03-07-1980
		BR 7908404 A	21-10-1980
		CA 1149583 A	12-07-1983
		IN 152405 A	07-01-1984
		JP 1511135 C	09-08-1989
		JP 55092123 A	12-07-1980
		JP 63057091 B	10-11-1988
		US 4452763 A	05-06-1984
		ZA 7906926 A	26-11-1980
GB 1102943 A		BE 675159 A	03-05-1966
		DE 1519944 A	07-08-1969
		FR 1463704 A	08-03-1967
		NL 6600868 A	06-10-1966
US 4039619 A	02-08-1977	CA 1043542 A	05-12-1978
		DE 2457909 A	17-07-1975
		GB 1497291 A	05-01-1978
		JP 50106871 A	22-08-1975
		MX 3158 E	22-05-1980